



**Automatización Eléctrica**

Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#)

## General Information

|                               |  |
|-------------------------------|--|
| <b>Extended Product Type:</b> | AF50-30-00RT 20-60V DC   |
| <b>Product ID:</b>            | 1SBL357010R7200  |
| <b>EAN:</b>                   | 3471522245120  |
| <b>Catalog Description:</b>   | AF50-30-00RT 20-60V DC Contactor   |
| <b>Long Description:</b>      | AF50 contactors are mainly used for controlling 3-phase motors and generally for controlling power circuits up to 690 V AC and 220 V DC. The contactors can also be used for many other applications such as bypass, capacitor switching, lighting, DC power circuits... The AF... contactors are fitted with an electronic coil interface which accepts a wide control voltage range, on AC 50/60 Hz or DC supplies. The same contactor can accept various supply voltages according to the different countries where the electrical equipment will be installed, or some fluctuation in the control voltage due to the local supply or network. The AF... contactors are also fully suitable for operation in AC or DC control circuit liable to voltage interruptions or voltage dip risks. Advantages: - Wide voltage range, e.g. 100 ... 250 V AC and DC - Can manage large voltage variations - Reduced power consumption - Very distinct closing and opening - Noise free - Can withstand voltage interruptions or voltage dips in the control supply ( $\leq 20$ ms). The AF... series 1-stack 3-pole contactors are of the block type design. - Main poles and auxiliary contact blocks: 3 main poles, front and side-mounted add-on auxiliary contact blocks - Control circuit: AC or DC operated - Accessories: a wide range of accessories is available. |

## Categories

Products » Low Voltage Products and Systems » Control Products » Contactors » Block Contactors

## Ordering

|                                |               |
|--------------------------------|---------------|
| <b>EAN:</b>                    | 3471522245120 |
| <b>Minimum Order Quantity:</b> | 1 piece       |
| <b>Customs Tariff Number:</b>  | 85369085      |

## Dimensions

|                            |          |
|----------------------------|----------|
| <b>Product Net Width:</b>  | 70 mm    |
| <b>Product Net Depth:</b>  | 108 mm   |
| <b>Product Net Height:</b> | 110 mm   |
| <b>Product Net Weight:</b> | 1.180 kg |

## Container Information

|                                      |               |
|--------------------------------------|---------------|
| <b>Package Level 1 Units:</b>        | 1 piece       |
| <b>Package Level 1 Width:</b>        | 140 mm        |
| <b>Package Level 1 Length:</b>       | 146 mm        |
| <b>Package Level 1 Height:</b>       | 96 mm         |
| <b>Package Level 1 Gross Weight:</b> | 1.18 kg       |
| <b>Package Level 1 EAN:</b>          | 3471522245120 |
| <b>Package Level 2 Units:</b>        | 20 piece      |

## Technical

|                       |                       |
|-----------------------|-----------------------|
| <b>Terminal Type:</b> | Ring-Tongue Terminals |
|-----------------------|-----------------------|

## Certificates and Declarations (Document Number)

|                          |                         |
|--------------------------|-------------------------|
| <b>EAC Certificate:</b>  | EAC_RU C-FR ME77 B01010 |
| <b>GOST Certificate:</b> | GOST_POCCFRME77B07175   |

## Classifications

|                |   |
|----------------|---|
| <b>ETIM 5:</b> | EC000066 - Magnet contactor, AC-switching |
| <b>UNSPSC:</b> | 39121529                                  |





**Automatización Eléctrica**  
Especialistas en Automatización

Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

| <b>Product</b>                   | <b>Code</b>     | <b>Reference</b> | <b>Product link</b>        |
|----------------------------------|-----------------|------------------|----------------------------|
| AF50-30-00RT 20-60V DC Contactor | 1SBL357010R7200 | AF50-30-00RT     | <a href="#">Buy on EAN</a> |