



Automatización Eléctrica
Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#)

General Information

Extended Product Type:	D2.5/5.3L
Product ID:	1SNA290036R2600
EAN:	3472592900360
Catalog Description:	D2.5/5.3L Spring Terminal Blocks - Feed-through with 3 connections - Black
Long Description:	D2.5/5.3L Spring Terminal Blocks - Feed-through - Black, 2.5mm ² RatedCrossSection, 5mm Spacing TH 35-7.5, TH 35-15 Rail

Categories

Products » Low Voltage Products and Systems » Connection Devices » Terminal Blocks » SNA Series

Ordering

Minimum Order Quantity:	50 piece
Customs Tariff Number:	85369010
Replacement Product ID (NEW):	1SNK705073R0000
EAN:	3472592900360

Dimensions

Product Net Height:	36.7 mm
Product Net Length:	36.7 mm
Product Net Depth:	36.7 mm
Product Net Weight:	7 g
Product Net Width:	5 mm

Container Information

Package Level 1 Width:	142 mm
Package Level 1 Length:	130 mm
Package Level 1 Height:	43 mm
Package Level 1 Gross Weight:	0.35 kg
Package Level 1 EAN:	3472592900360
Package Level 2 Units:	1500 piece
Package Level 2 Width:	300 mm
Package Level 2 Length:	500 mm
Package Level 2 Height:	300 mm
Package Level 2 Gross Weight:	11.000 kg
Package Level 3 Units:	36000 piece
Product Packing Type:	Box
Package Level 1 Units:	50 piece

Technical

Spacing:	5 mm
Connection Type:	Spring
Function:	Feed-through
Number of Levels:	1
Connecting Capacity-Main Circuit:	Spring Clamp / Flexible 1x 0.12 ... 2.5 mm ² Spring Clamp / Rigid 1x 0.12 ... 4 mm ² Spring Clamp / With Insulated Ferrule 1x 0.5 ... 1.5 mm ²
Gauge Type:	A2
Rated Current (I _n):	Main Circuit 24 A
Rated Short-time Withstand Current (I _{cw}):	for 1 s 300 A
Rated Voltage (U _r):	800 V
Rated Impulse Withstand Voltage (U _{imp}):	8000 V
Dielectric Test Voltage:	3000 V
Pollution Degree:	3
Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20
Insulation Material:	Polyamide
Mounting on DIN Rail:	TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
Wire Stripping Length:	9.5 mm
Recommended Screw Driver:	3.5 mm

Rated Cross-Section:	2.5 mm ²
-----------------------------	---------------------

Technical UL/CSA

Connecting Capacity Main Circuit UL/CSA:	Spring Clamp / Flexible 1x 26 ... 12 AWG Spring Clamp / Rigid 1x 26 ... 12 AWG
Connecting Capacity UL/CSA:	Stranded 12 AWG
Flammability According to UL94:	V0
Maximum Operating Voltage UL/CSA:	Main Circuit 600 V

Environmental

RoHS Status:	Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2007 Q4
Ambient Air Temperature:	Operation -55 ... +110 °C Storage -55 ... +110 °C

Certificates and Declarations (Document Number)

cUL Certificate:	1SND162000A0204
Declaration of Conformity - CE:	1SND225016C1007
EAC Certificate:	1SND162001A1100
RoHS Information:	1SND230488F0201

Classifications

ETIM 4:	EC000897 - Feed-through terminal block
ETIM 5:	EC000897 - Feed-through terminal block
Object Classification Code:	X



Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

Product	Code	Reference	Product link
D2.5/5.3L Spring Terminal Blocks - Feed-through with 3 connections - Black	1SNA290036R2600	D2.5/5.3LNG	Buy on EAN