



**Automatización Eléctrica**  
Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#)

## General Information

|                        |   |
|------------------------|---|
| Extended Product Type: | ZS4-S   |
| Product ID:            | 1SNK505310R0000   |
| EAN:                   | 3472595053100   |
| Catalog Description:   | ZS4-S Screw Clamp Terminal Block - Disconnect with blade - Grey   |
| Long Description:      | ZS4-S Screw Clamp Terminal Block - Disconnect with Blade - Grey, 4mm <sup>2</sup> RatedCrossSection, 5.2mmSpacing, TH 35-7.5, TH 35-15 Rail |

## Categories

Products » Low Voltage Products and Systems » Connection Devices » Terminal Blocks » SNK Series

## Ordering

|                         |               |
|-------------------------|---------------|
| Minimum Order Quantity: | 50 piece      |
| Customs Tariff Number:  | 85369010      |
| EAN:                    | 3472595053100 |

## Dimensions

|                     |          |
|---------------------|----------|
| Product Net Height: | 53 mm    |
| Product Net Length: | 51.35 mm |
| Product Net Depth:  | 51.4 mm  |
| Product Net Weight: | 8.6 g    |
| Product Net Width:  | 5.2 mm   |

## Container Information

|                               |               |
|-------------------------------|---------------|
| Package Level 1 Width:        | 54 mm         |
| Package Level 1 Length:       | 252 mm        |
| Package Level 1 Height:       | 52 mm         |
| Package Level 1 Gross Weight: | 0.43 kg       |
| Package Level 1 EAN:          | 3472595053100 |
| Package Level 2 Units:        | 900 piece     |
| Package Level 2 Width:        | 300 mm        |
| Package Level 2 Length:       | 400 mm        |
| Package Level 2 Height:       | 200 mm        |
| Package Level 2 Gross Weight: | 8.240 kg      |
| Package Level 3 Units:        | 43200 piece   |
| Product Packing Type:         | Box           |
| Package Level 1 Units:        | 50 piece      |

## Technical

|  |  |
|--|--|
| Spacing:   | 5.2 mm   |
| Connection Type:                                       | Screw clamp  |
| Function:  | Disconnect   |
| Number of Levels:                                      | 1  |
| Connecting Capacity-Main Circuit:                      | Screw Clamp / Flexible 1x 0.2 ... 4 mm <sup>2</sup><br>Screw Clamp / Flexible 2x 0.2 ... 1.5 mm <sup>2</sup><br>Screw Clamp / Rigid 1x 0.2 ... 4 mm <sup>2</sup><br>Screw Clamp / Rigid 2x 0.2 ... 1.5 mm <sup>2</sup><br>Screw Clamp / With Insulated Ferrule 1x 0.22 ... 2.5 mm <sup>2</sup><br>Screw Clamp / Without Insulated Ferrule 1x 0.22 ... 4 mm <sup>2</sup><br>Screw Clamp / With Twin Ferrule 2x 0.22 ... 1.5 mm <sup>2</sup> |
| Gauge Type:  | A3-B3  |
| Rated Current (I <sub>n</sub> ):                       | Main Circuit 25 A  |
| Rated Short-time Withstand Current (I <sub>cw</sub> ): | for 1 s 480 A  |
| Rated Voltage (U <sub>r</sub> ):                       | 400 V  |
| Rated Impulse Withstand Voltage (U <sub>imp</sub> ):   | 6000 V   |
| Dielectric Test Voltage:                               | 1890 V   |
| Pollution Degree:                                      | 3  |
| Power Loss:  | 0.8 W  |
| Degree of Protection:                                  | acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20   |
| Insulation Material:                                   | Polyamide  |
| Mounting on DIN Rail:                                  | TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715   |

|                                  |  |
|----------------------------------|--|
|                                  | TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 |
| <b>Wire Stripping Length:</b>    | 10.5 mm  |
| <b>Recommended Screw Driver:</b> | 3.5 mm   |
| <b>Rated Cross-Section:</b>      | 4 mm <sup>2</sup>                                    |

### Technical UL/CSA

|   |   |
|---|---|
| <b>Connecting Capacity Main Circuit UL/CSA:</b> | Screw Clamp / Flexible 1x 24 ... 10 AWG<br>Screw Clamp / Flexible 2x 24 ... 16 AWG<br>Screw Clamp / Rigid 1x 24 ... 10 AWG<br>Screw Clamp / Rigid 2x 24 ... 16 AWG<br>Screw Clamp / With Insulated Ferrule 1x 24 ... 14 AWG<br>Screw Clamp / Without Insulated Ferrule 1x 24 ... 10 AWG<br>Screw Clamp / With Twin Ferrule 2x 24 ... 16 AWG |
| <b>Connecting Capacity UL/CSA:</b>              | Stranded 10 AWG   |
| <b>Flammability According to UL94:</b>          | V0  |
| <b>Maximum Operating Voltage UL/CSA:</b>        | Main Circuit 150 V  |

### Environmental

|  |   |
|--|---|
| <b>Resistance to Vibrations acc. to IEC 60068-2-6:</b> | Compliant   |
| <b>RoHS Status:</b>                                    | Following EU Directive 2002/95/EC August 18, 2005 and amendment |
| <b>Ambient Air Temperature:</b>                        | Operation -55 ... +110 °C<br>Storage -55 ... +110 °C            |

### Certificates and Declarations (Document Number)

|  |                 |
|--|-----------------|
| <b>BV Certificate:</b>                 | 1SND161073A0203 |
| <b>CB Certificate:</b>                 | 1SND161078A0200 |
| <b>CSA Certificate:</b>                | 1SND161070A0208 |
| <b>cUL Certificate:</b>                | 1SND161040A0206 |
| <b>Declaration of Conformity - CE:</b> | 1SND225099C1005 |
| <b>DNV Certificate:</b>                | 1SND161087A0202 |
| <b>EAC Certificate:</b>                | 1SND161009A1100 |
| <b>RINA Certificate:</b>               | 1SND161088A0200 |
| <b>RoHS Information:</b>               | 1SND230491F0206 |

### Classifications

|                                    |  |
|------------------------------------|--|
| <b>E-nummer:</b>                   | 2925915                                      |
| <b>ETIM 4:</b>                     | EC000902 - (Knife) disconnect terminal block |
| <b>ETIM 5:</b>                     | EC000902 - (Knife) disconnect terminal block |
| <b>Object Classification Code:</b> | X  |



Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

| <b>Product</b>  | <b>Code</b>     | <b>Reference</b> | <b>Product link</b>        |
|---|-----------------|------------------|----------------------------|
| ZS4-S Screw Clamp Terminal Block - Disconnect with blade - Grey | 1SNK505310R0000 | ZS4-S            | <a href="#">Buy on EAN</a> |