



Automatización Eléctrica
Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#)

General Information

Extended Product Type:	ZS10-ST
Product ID:	1SNK508310R0000
EAN:	3472595083107
Catalog Description:	ZS10-ST Screw terminal block- Test disconnect with sliding link- Grey
Long Description:	ZS10-ST Screw Clamp Terminal Block - Disconnect with sliding link - Grey, 10mm ² RatedCrossSection, 8mmSpacing, TH 35-7.5, TH 35-15 Rail

Categories

Products » Low Voltage Products and Systems » Connection Devices » Terminal Blocks » SNK Series

Ordering

EAN:	3472595083107
Minimum Order Quantity:	25 piece
Customs Tariff Number:	85369010

Dimensions

Product Net Width:	8 mm
Product Net Height:	80.7 mm
Product Net Length:	52 mm
Product Net Depth:	52 mm
Product Net Weight:	24.8 g

Container Information

Package Level 1 Units:	25 piece
Package Level 1 Width:	82 mm
Package Level 1 Height:	65 mm
Package Level 1 Length:	265 mm
Package Level 1 Gross Weight:	0.62 kg
Package Level 1 EAN:	3472595083107
Package Level 2 Units:	250 piece
Package Level 2 Width:	300 mm
Package Level 2 Height:	200 mm
Package Level 2 Length:	400 mm
Package Level 3 Units:	12000 piece
Product Packing Type:	Box

Environmental

Ambient Air Temperature:	Operation -55 ... +110 °C Storage -55 ... +110 °C
RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment

Technical UL/CSA

Maximum Operating Voltage UL/CSA:	Main Circuit 300 V
Connecting Capacity Main Circuit UL/CSA:	Screw Clamp / Flexible 1x 24 ... 6 AWG Screw Clamp / Flexible 2x 20 ... 12 AWG Screw Clamp / Rigid 1x 24 ... 6 AWG Screw Clamp / Rigid 2x 20 ... 12 AWG Screw Clamp / With Insulated Ferrule 1x 24 ... 10 AWG Screw Clamp / Without Insulated Ferrule 1x 24 ... 8 AWG Screw Clamp / With Twin Ferrule 2x 20 ... 12 AWG
Connecting Capacity UL/CSA:	Stranded 6 AWG
Flammability According to UL94:	V0

Additional Information

Ambient Temperature:	-5 ... +40 °C
Color:	Grey
Connecting Capacity-Main Circuit:	Screw Clamp / Flexible 1x 0.5 ... 10 mm ² Screw Clamp / Flexible 2x 0.5 ... 4 mm ² Screw Clamp / Rigid 1x 0.5 ... 10 mm ² Screw Clamp / Rigid 2x 0.5 ... 4 mm ² Screw Clamp / With Insulated Ferrule 1x 0.5 ... 6 mm ² Screw Clamp / Without Insulated Ferrule 1x 0.5 ... 10 mm ²

Screw Clamp / With Twin Ferrule 2x 0.5 ... 4 mm²

Connection Type:	Screw clamp
Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20
Dielectric Test Voltage:	2000 V
Function:	Disconnect
Gauge Type:	A5-B5
IIT Publishing Status:	Level 0 - Information enabled
Insulation Material:	Polyamide
Mounting on DIN Rail:	TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
Number of Levels:	1
Pollution Degree:	3
Power Loss:	2.6 W
Product Main Type:	ZS10-ST
Product Name:	Terminal Block
Rated Cross-Section:	10 mm ²
Rated Current (I_n):	Main Circuit 50 A
Rated Impulse Withstand Voltage (U_{imp}):	8000 V
Rated Short-time Withstand Current (I_{cw}):	for 1 s 1200 A
Rated Voltage (U_r):	630 V
Recommended Screw Driver:	3.5 mm
RoHS Date:	20050818
Spacing:	8 mm
Sub-Function:	With sliding link
Sub-Function 3:	With sliding link
Wire Stripping Length:	13.0 mm

Certificates and Declarations (Document Number)

BV Certificate:	1SND161073A0203
CB Certificate:	1SND161091A0200
CSA Certificate:	1SND161070A0208
cUL Certificate:	1SND161041A0207
Data Sheet, Technical Information:	1SNK161056D0201
Declaration of Conformity - CE:	1SND225113C1001
DNV Certificate:	1SND161087A0202
EAC Certificate:	1SND161009A1100
RoHS Information:	1SND230516F0201

Classifications

ETIM 4:	EC000902 - (Knife) disconnect terminal block
ETIM 5:	EC000902 - (Knife) disconnect terminal block
Object Classification Code:	X



Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

Product	Code	Reference	Product link
ZS10-ST Screw terminal block- Test disconnect with sliding link- Grey	1SNK508310R0000	ZS10-ST	Buy on EAN