



At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking HERE



### **General Information**

Extended Product Type: ZS16-BL

 Product ID:
 1SNK510020R0000

 EAN:
 3472595100200

Catalog Description: ZS16-BL Screw Clamp Terminal Block - Feed-through - Blue

Long Description: ZS16-BL Screw Clamp Terminal Block - Feed-through - Blue, 16mm² RatedCrossSection,

10mmSpacing, TH 35-7.5, TH 35-15 Rail

# Categories

Products » Low Voltage Products and Systems » Connection Devices » Terminal Blocks » SNK Series

### Ordering

 Minimum Order Quantity:
 25 piece

 Customs Tariff Number:
 85369010

 EAN:
 3472595100200

#### **Dimensions**

Product Net Height: 56.1 mm

Product Net Length: 48.8 mm

Product Net Depth: 48.8 mm

Product Net Weight: 20.2 g

Product Net Width: 10 mm

#### **Container Information**

Package Level 1 Width: 52 mm Package Level 1 Length: 259 mm Package Level 1 Height: 50 mm Package Level 1 Gross Weight: 0.505 kg Package Level 1 EAN: 3472595100200 Package Level 2 Units: 450 piece Package Level 2 Width: 300 mm Package Level 2 Length: 400 mm Package Level 2 Height: 200 mm Package Level 2 Gross Weight: 9.680 kg Package Level 3 Units: 21600 piece **Product Packing Type:** Box Package Level 1 Units: 25 piece

# **Technical**

Spacing:10 mmConnection Type:Screw clampFunction:Feed-through

Number of Levels: 1

Connecting Capacity-Main Circuit: Screw Clamp / Flexible 1x 0.5 ... 16 mm²

Screw Clamp / Flexible 2x 0.5 ... 6 mm<sup>2</sup> Screw Clamp / Rigid 1x 0.5 ... 16 mm<sup>2</sup> Screw Clamp / Rigid 2x 0.5 ... 6 mm<sup>2</sup>

Screw Clamp / With Insulated Ferrule 1x 0.5 ... 10 mm<sup>2</sup> Screw Clamp / Without Insulated Ferrule 1x 0.5 ... 16 mm<sup>2</sup> Screw Clamp / With Twin Ferrule 2x 0.5 ... 6 mm<sup>2</sup>

Gauge Type: A6-B6

Rated Current (I<sub>n</sub>): Main Circuit 76 A

Rated Short-time Withstand Current for 1 s 1920 A

(I<sub>cw</sub>):

Rated Voltage ( $U_r$ ): 1000 V

Rated Impulse Withstand Voltage

(U<sub>imp</sub>):

8000 V

Dielectric Test Voltage: 2200 V
Pollution Degree: 3
Power Loss: 2.4 W

Degree of Protection: acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20

Insulation Material: Polyamide

Mounting on DIN Rail: TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715

TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715

Wire Stripping Length: 13.5 mm **Recommended Screw Driver:** 5.5 mm Rated Cross-Section: 16 mm<sup>2</sup>

## Technical UL/CSA

**Connecting Capacity Main Circuit** 

UL/CSA:

Screw Clamp / Flexible 1x 24 ... 4 AWG Screw Clamp / Flexible 2x 20 ... 10 AWG Screw Clamp / Rigid 1x 24 ... 4 AWG Screw Clamp / Rigid 2x 20 ... 10 AWG

Screw Clamp / With Insulated Ferrule 1x 24 ... 8 AWG Screw Clamp / Without Insulated Ferrule 1x 24 ... 4 AWG Screw Clamp / With Twin Ferrule 2x 20 ... 10 AWG

Connecting Capacity UL/CSA: Stranded 4 AWG

Flammability According to UL94: V0 Short-Circuit Current Rating (SCCR): 100 kA

**Maximum Operating Voltage** 

UL/CSA:

Main Circuit 600 V

### **Environmental**

Resistance to Vibrations acc. to IEC Compliant

60068-2-6:

**RoHS Status:** Following EU Directive 2002/95/EC August 18, 2005 and amendment

**Ambient Air Temperature:** Operation -55 ... +110 °C

Storage -55 ... +110 °C

## **Certificates and Declarations (Document Number)**

| ATEX Certificate:               | 1SND162004A1706 |
|---------------------------------|-----------------|
| BV Certificate:                 | 1SND161073A0203 |
| CB Certificate:                 | 1SND161021A0201 |
| CSA Certificate:                | 1SND161070A0208 |
| cUL Certificate:                | 1SND161040A0206 |
| Declaration of Conformity - CE: | 1SND225081C1013 |
| DNV Certificate:                | 1SND161087A0202 |
| RINA Certificate:               | 1SND161088A0200 |
| RoHS Information:               | 1SND230491F0206 |

# Classifications

| Oldoomodilono               |  |
|-----------------------------|--|
| E-nummer:                   | 2925975                                |
| ETIM 4:                     | EC000897 - Feed-through terminal block |
| ETIM 5:                     | EC000897 - Feed-through terminal block |
| Object Classification Code: | X                                      |







Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, click on the green button.

| Product  | Code            | Reference | Product link |
|--|-----------------|-----------|--------------|
| ZS16-BL Screw Clamp Terminal Block - Feed-<br>through - Blue | 1SNK510020R0000 | ZS16-BL   | Buy on EAN   |