

Reference: 3RA1316-8XB30-1AD0

REVERSING CONTACTOR ASSEMBLY
AC-3, 4KW/400 V, 3-POLE, SZ. S00
SCREW CONNECTION, AC 42V, 50/60 HZ
ELECTR. AND MECH. INTERLOCKING

Buy it at [Electric Automation Network](#)



General technical data:	
Product function	reversing contactor
Size of contactor	S00
Width	mm 90
Height	mm 67
Depth	mm 72
Equipment marking acc. to DIN EN 61346-2	Q
Equipment marking acc. to DIN 40719 extended according to IEC 204-2 acc. to IEC 750	K
Control circuit/ Control:	
Type of voltage of the control supply voltage	AC
Control supply voltage 1	
at AC	
— at 50 Hz rated value	V 42
— at 60 Hz rated value	V 42
Control supply voltage frequency	
1 rated value	Hz 50
2 rated value	Hz 60
Main circuit:	
Operating current at AC-3 at 400 V rated value	A 9
Operating power at AC-3 at 400 V rated value	kW 4

Auxiliary circuit:			
Number of NC contacts for auxiliary contacts per direction of rotation	0		
Number of NO contacts for auxiliary contacts per direction of rotation	0		
Connections/ Terminals:			
Type of electrical connection for main current circuit	screw-type terminals		
Mounting type	screw and snap-on mounting onto 35 mm standard mounting rail according to DIN EN 50022		
Ambient conditions:			
Ambient temperature during operation	°C -25 ... +60		
Protection class IP on the front	IP20		
Certificates/ approvals:			
General Product Approval	Declaration of Conformity	Test Certificates	Shipping Approval
		spezielle Prüfbescheinigungen	
Shipping Approval			
other			
Umweltbestätigung	Bestätigungen		