



PRODUCT-DETAILS

3GAA071001-CSE

M2AA 71 A-2

General Information

Product ID	3GAA071001-CSE
ABB Type Designation	M2AA 71A 2
Catalog Description	M2AA 71 A-2
Long Description	M2AA 71 A-2

Additional Information

ABB Type Designation	M2AA 71A 2
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6203-2Z/C3
Bearing NDE	6202-2Z/C3
Country of Origin	China (CN) Poland (PL)
Customs Tariff Number	85015100
Direction of Rotation	Both sides

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
D	--	50 Hz	230 V	0.37 kW	2800 r/min	1.65 A	0.760	73.80 %	1.26 N·m	5.10
Y	--	50 Hz	400 V	0.37 kW	2800 r/min	0.95 A	0.760	73.80 %	1.26 N·m	5.10
Y	--	60 Hz	460 V	0.37 kW	3400 r/min	0.84 A	0.710	77.50 %	1.05 N·m	6.30

Gross Weight	4.9 kg
IC Class	IC411
IM Class	IMB14 IM3601
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M2AA 71 A-2
Lubrication	For life
Made To Order	No
Medium Description	M2AA 71 A-2
Minimum Order Quantity	1 piece
Moment of Inertia	0.00035 kg/m ³
Number of Poles (High)	2
Order Multiple	1 piece

Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	4.9 kg
Product Type	2AA2__M2AA__IE2_AA
Quote Only	No
Selling Unit of Measure	piece
Short Description	M2AA 71 A-2
Sound dB (A)	58 dB(A)
Standards	IEC 60034-1
Starting of Motor	Direct Online
Stocked At (Warehouses)	Central Stock Europe Central Stock Spain
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
Voltage Code	S
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)