



Fuse-link, low voltage, 175 A, DC 72 V, 92.33 x 27 mm

Catalog No. **ACK-175**

Similar to illustration

### Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	175
Rated voltage			DC 72 V
Size			92.33 x 27 mm
usable for size/applications			fork-lift trucks, marine and other battery-operated systems

### Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])			
Construction size			Other
Rated current		A	175
Rated voltage		V	72
Voltage type			DC
Voltage type			DC
Rated switching capacity		kA	10
Utilization category			Other
Type of fuse status indicator			None
Insulated metal gripping lugs (IMGL)			No

### Additional product information (links)

Product datasheet (pdf)	<a href="http://www.cooperindustries.com/content/dam/public/bussmann/Edison/Resources/Catalogs/Bus_Edison_ACK_ACL_ACS.pdf">http://www.cooperindustries.com/content/dam/public/bussmann/Edison/Resources/Catalogs/Bus_Edison_ACK_ACL_ACS.pdf</a>
-------------------------	---