

Variable frequency drive, 400 V AC, 3-phase, 55 kW, IP21, Radio interference suppression filter, Brake chopper, OLED display, FR8

**Part no. SPX075A1-4A1B1
138608**

General specifications	
Product name	Eaton SPX variable frequency drive
Part no.	SPX075A1-4A1B1
EAN	4015081353880
Product Length/Depth	758 millimetre
Product height	344 millimetre
Product width	291 millimetre
Product weight	58 kilogram
Certifications	Certified by UL for use in Canada IEC/EN61800-5 Specification for general requirements: IEC/EN 61800-2 CUL UL 508C Safety: EN 61800-5-1: 2003 RoHS, ISO 9001 DNV RCM CSA-C22.2 No. 14 UL report applies to both US and Canada IEC/EN 61800-3 UL File No.: E134360 UL CE CSA Class No.: 3211-06 UL Category Control No.: NMMS, NMMS2, NMMS7, NMMS8 IEC/EN61800-3
Product Tradename	SPX
Product Type	Variable frequency drive
Product Sub Type	None
Catalog Notes	Assigned motor rating: For AC motors with internal and external ventilation with 50 Hz / 60 Hz Assigned motor rating: Overload cycle for 60 s every 600 s Mains choke recommended only if the power quality is poor. Current harmonics (THD) are attenuated by internal DC link chokes.
General information	
Degree of protection	IP21 NEMA Other
Electromagnetic compatibility	1st and 2nd environments (according to EN 61800-3)
Fitted with:	DC link choke Internal DC link Brake chopper IGBT inverter OLED display Radio interference suppression filter
Frame size	FR8
Mounting position	Vertical
Product Category	Variable frequency drives
Protection	Finger and back-of-hand proof, Protection against direct contact (BGV A3, VBG4)
Radio interference class	C2, C3: depending on the motor cable length, the connected load, and ambient conditions. External radio interference suppression filters (optional) may be necessary.
Suitable for	Branch circuits, (UL/CSA)
Climatic environmental conditions	
Altitude	Above 1000 m with 1 % performance reduction per 100 m Max. 1000 m Max. 3000 m
Ambient operating temperature - min	-10 °C
Ambient operating temperature - max	50 °C
Ambient operating temperature at 150% overload - min	-10 °C
Ambient operating temperature at 150% overload - max	50 °C

Ambient storage temperature - min		-40 °C
Ambient storage temperature - max		70 °C
Climatic proofing		< 95 % relative humidity, no condensation, no corrosion, no dripping water
Main circuit		
Mains voltage - min		380 V
Mains voltage - max		500 V
Operating mode		Optional: Vector control with feedback (CLV) U/f control Sensorless vector control (SLV)
Output frequency - min		0 Hz
Output frequency - max		320 Hz
Output voltage (U2)		400 V AC, 3-phase 480 V AC, 3-phase 500 V AC, 3-phase
Rated control supply voltage		10 V DC (Us, max. 10 mA)
Rated frequency - min		45 Hz
Rated frequency - max		66 Hz
Rated operational current (Ie) at 110% overload		140 A
Rated operational current (Ie) at 150% overload		105 A
Rated operational power at 380/400 V, 50 Hz		55 kW
Rated operational power at 380/400 V, 50 Hz, 110% overload		75 kW
Rated operational voltage		400 V AC, 3-phase 500 V AC, 3-phase 480 V AC, 3-phase
Resolution		0.01 Hz (Frequency resolution, setpoint value)
Supply frequency		50/60 Hz
Switching frequency		3.6 kHz, 1 - 10 kHz adjustable, fPWM, Power section, Main circuit
System configuration type		AC supply systems with earthed center point
Voltage rating - max		480 V AC
Motor rating		
Assigned motor current IM at 400 V, 50 Hz, 110% overload		134 A
Assigned motor current IM at 400 V, 50 Hz, 150% overload		99 A
Assigned motor current IM at 440 - 480 V, 60 Hz, 150% overload		96 A
Assigned motor current IM at 440/480 V, 60 Hz, 110% overload		124 A
Assigned motor power at 460/480 V, 60 Hz		75 HP
Assigned motor power at 460/480 V, 60 Hz, 110% overload		100 HP
Control circuit		
Number of inputs (analog)		2 (parameterizable, 0 - 10 V DC, 0/4 - 20 mA)
Number of inputs (digital)		6 (parameterizable, max. 30 V DC)
Number of outputs (analog)		1
Number of outputs (digital)		1 (parameterizable, 48 V DC/50 mA)
Number of relay outputs		2 (parameterizable, N/O, 8 A (24 V DC) / 8 A (250 V AC) / 0,4 A (125 V DC))
Rated control voltage (Uc)		24 V DC (external, max. 250 mA)
Communication		
Communication interface		BACnet/IP, optional CANopen®, optional LonWorks, optional Modbus-TCP, optional PROFIBUS-DP DeviceNet, optional BACnet MS/TP, optional EtherCAT, optional Ethernet IP, optional Modbus-RTU, optional PROFINET, optional
Connection to SmartWire-DT		No
Design verification		
Equipment heat dissipation, current-dependent Pvid		1375 W
Heat dissipation capacity Pdis		0 W
Heat dissipation per pole, current-dependent Pvid		0 W
Rated operational current for specified heat dissipation (In)		105 A

Static heat dissipation, non-current-dependent Pvs			0 W
Heat dissipation details			Operation (with 150 % overload)
10.2.2 Corrosion resistance			Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures			Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat			Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects			Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation			Meets the product standard's requirements.
10.2.5 Lifting			Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact			Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions			Meets the product standard's requirements.
10.3 Degree of protection of assemblies			Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances			Meets the product standard's requirements.
10.6 Incorporation of switching devices and components			Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections			Is the panel builder's responsibility.
10.8 Connections for external conductors			Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength			Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage			Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material			Is the panel builder's responsibility.
10.10 Temperature rise			The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.