

Surface-mounting enclosure, RAL 1004, With additional cable entry in front for M22-XPV60... illuminated ring, Number of locations: 1, Cable entry: rear: 1 x M20, lateral: 1 x M20

Part no. **M22-IY1-XPV60-\***  
**197630**

| <b>General specifications</b>   |  |   |
|---------------------------------|--|---|
| Product name                    |  | Eaton Moeller® series M22 Accessory Surface mounting enclosure                            |
| Part no.                        |  | M22-IY1-XPV60-*   |
| Product Length/Depth            |  | 70 millimetre   |
| Product height                  |  | 30 millimetre   |
| Product width                   |  | 80 millimetre   |
| Product weight                  |  | 0.157 kilogram  |
| Compliances                     |  | CE  |
| Product Tradename               |  | M22   |
| Product Type                    |  | Accessory   |
| Product Sub Type                |  | Surface mounting enclosure  |
| Catalog Notes                   |  | Individually markable with pushbutton configurator  |
| <b>Features &amp; Functions</b> |  |   |
| Enclosure color                 |  | Yellow  |
| Enclosure material              |  | Plastic   |
| Fitted with:                    |  | High-grade steel screws<br>Cable entry in front for M22-XPV60...                          |
| Knockouts                       |  | 1 x M20 (cable entry knockout at the side)<br>1 x M20 (cable entry knockouts at the rear) |
| Number of locations             |  | 1   |
| RAL-number                      |  | 1004  |
| <b>General information</b>      |  |   |
| Degree of protection            |  | IP67/IP69K<br>NEMA 4X   |
| Opening diameter                |  | 22.5 mm   |
| <b>Communication</b>            |  |   |
| Connection to SmartWire-DT      |  | No  |

## Technical data ETIM 9.0

| Low-voltage industrial components (EG000017) / Enclosure for control circuit devices (EC000200)   |    |                         |
|---|----|-------------------------|
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Housing for command and alarm devices (ecl@ss13-27-37-12-05 [AKF023019]) |    |                         |
| Number of command positions   |    | 1                       |
| Construction type housing   |    | Surface mounted housing |
| Housing material  |    | Plastic                 |
| Housing material quality  |    | Other                   |
| Diameter openings   | mm | 22.5                    |
| Colour housing cover  |    | Yellow                  |
| Degree of protection (IP)   |    | IP67/IP69K              |
| Degree of protection (NEMA)   |    | 4X                      |
| Width   | mm | 80                      |
| Height  | mm | 30                      |
| Depth   | mm | 70                      |