



Fuse-link, low voltage, 32 A, AC 660 V, DC 460 V, BS88/A4, 23 x 109 mm, gL/gG, BS

TCP32A

Product name	Eaton Bussmann series low voltage British standard fuse
Part no.	TCP32A
EAN	5027590513425
Product Length/Depth	109 millimetre
Product height	23 millimetre
Product width	23 millimetre
Product weight	83.6 gram
Compliances	RoHS Compliant CE Marked
Certifications	IEC 60269 EAC BS88
Product Tradename	None
Product Type	Low voltage British standard fuse
Product Sub Type	None
Amperage Rating	32 A
Voltage rating	690 Vac, 460 Vdc
Voltage type	AC/DC
Breaking capacity	80 kA
Class	Class gG/gL
Application	general industrial applications
Fuse type	TCP
Fuse size	BS88/A4
Fitted with:	Offset bolted tags
Connection	94 mm fixing centre
Suitable for	RS100 Red spot fuse holder

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011])		
Fuse construction type according to IEC 60269		A4
Type of current		AC/DC
Rated voltage AC	V	660
Rated voltage DC	V	460
Rated current	A	32
Utilization category		gL/gG (cable protection/equipment protection)
Breaking capacity	kA	80
Colour code		None
Type of fuse status indicator		None
Power loss at rated current	W	
Mounting holes		M8
Centre-to-centre distance of connections	mm	93.7