

Lens, indicator light, flat, green



**Part no.**                    **L25LF-GN**  
**025422**

| <b>General specifications</b>  |  |
|--|--|
| Product name   | Eaton Moeller® series RMQ16 Accessory Lens   |
| Part no.   | L25LF-GN   |
| EAN  | 4015080254225  |
| Product Length/Depth   | 5 millimetre   |
| Product height   | 21 millimetre  |
| Product width  | 21 millimetre  |
| Product weight   | 0.002 kilogram   |
| Compliances  | CE   |
| Product Tradename  | RMQ16  |
| Product Type   | Accessory  |
| Product Sub Type   | Lens   |
| <b>Features &amp; Functions</b>  |  |
| Design   | Flat   |
| Fitted with:   | Customized inscription using the Label Editor  |
| Lens color   | Green  |
| <b>General information</b>   |  |
| Product category   | Accessories  |
| Type   | Lenses for indicator lights  |
| <b>Communication</b>   |  |
| Connection to SmartWire-DT   | No   |
| <b>Design verification</b>   |  |
| Equipment heat dissipation, current-dependent Pvid                               | 0 W  |
| Heat dissipation capacity Pdis   | 0 W  |
| Heat dissipation per pole, current-dependent Pvid                                | 0 W  |
| Rated operational current for specified heat dissipation (In)                    | 0 A  |
| Static heat dissipation, non-current-dependent Pvs                               | 0 W  |
| 10.2.2 Corrosion resistance  | Meets the product standard's requirements.   |
| 10.2.3.1 Verification of thermal stability of enclosures                         | Meets the product standard's requirements.   |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat       | Meets the product standard's requirements.   |
| 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects | Meets the product standard's requirements.   |
| 10.2.4 Resistance to ultra-violet (UV) radiation                                 | Please enquire   |
| 10.2.5 Lifting   | Does not apply, since the entire switchgear needs to be evaluated.                             |
| 10.2.6 Mechanical impact   | Does not apply, since the entire switchgear needs to be evaluated.                             |
| 10.2.7 Inscriptions  | Meets the product standard's requirements.   |
| 10.3 Degree of protection of assemblies  | Does not apply, since the entire switchgear needs to be evaluated.                             |
| 10.4 Clearances and creepage distances   | Meets the product standard's requirements.   |
| 10.5 Protection against electric shock   | Does not apply, since the entire switchgear needs to be evaluated.                             |
| 10.6 Incorporation of switching devices and components                           | Does not apply, since the entire switchgear needs to be evaluated.                             |
| 10.7 Internal electrical circuits and connections                                | Is the panel builder's responsibility.   |
| 10.8 Connections for external conductors   | Is the panel builder's responsibility.   |
| 10.9.2 Power-frequency electric strength   | Is the panel builder's responsibility.   |
| 10.9.3 Impulse withstand voltage   | Is the panel builder's responsibility.   |
| 10.9.4 Testing of enclosures made of insulating material                         | Is the panel builder's responsibility.   |
| 10.10 Temperature rise   | Not applicable.  |
| 10.11 Short-circuit rating   | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.12 Electromagnetic compatibility  | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |

## Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Hood/lens for circuit control devices (EC001072)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Dome, refractor (ecI@ss13-27-37-12-31 [AKF049019])

|                   |  |    |        |
|-------------------|--|----|--------|
| Colour lens       |  |    | Green  |
| Shape of lens     |  |    | Square |
| Construction type |  |    | Flat   |
| Labelled          |  |    | No     |
| Built-in diameter |  | mm | 16     |
| Diameter          |  | mm | 0      |
| Width             |  | mm | 21     |
| Height            |  | mm | 21     |