

4-pole busbar system xClic, 250A

Part no. **BPZ-KB-12/250**
184977

General specifications		
Product name		Eaton xEnergy Basic other accessory
Part no.		BPZ-KB-12/250
EAN		4015081804030
Product Length/Depth		51 millimetre
Product height		84 millimetre
Product width		232 millimetre
Product weight		0.57 kilogram
Compliances		RoHS conform
Product Tradename		xEnergy Basic
Product Type		Accessories
Product Sub Type		Other
Delivery program		
Amperage rating		250 A
Number of poles		Four-pole
Technical Data - Mechanical		
Number of clamp positions per pole		6
Conductor cross section (solid, solid-strand) - min		0 mm ²
Conductor cross section (solid, solid-strand) - max		0 mm ²
Additional information		
Fitted with:		N-rail

Technical data ETIM 9.0

Energy distribution systems (EG000015) / Distributor assembly terminal blocks (EC001894)			
Electric engineering, automation, process control engineering / Electrical insulation and connecting material / Energy distribution system / Distributor assembly terminal blocks (ecI@ss13-27-40-06-09 [AC0381016])			
Height		mm	84
Width		mm	232
Depth		mm	51
Max. rated current		A	250
Number of poles			4
Conductor cross section flexible (fine-strand) with cable end sleeve		mm ²	1.5 - 10
Conductor cross section solid (solid, stranded)		mm ²	0 - 0
Number of clamp positions per pole			6
With PE-rail			No
With N-rail			Yes