Surface-mounting enclosure, RAL 7035, Individually markable with pushbutton configurator, Number of locations: 4, Cable entry: rear: $2 \times M20$, at top: $2 \times M20$, lateral: $2 \times M20/M25$ ($1 \times each side$)



Part no. M22-I4-* 197635

General specifications	
Product name	Eaton Moeller® series M22 Accessory Surface mounting enclosure
Part no.	M22-I4-*
Product Length/Depth	80 millimetre
Product height	56 millimetre
Product width	186 millimetre
Product weight	0.279 kilogram
Compliances	CE
Product Tradename	M22
Product Type	Accessory
Product Sub Type	Surface mounting enclosure
Catalog Notes	Individually markable with pushbutton configurator
Features & Functions	
Enclosure color	Gray
Enclosure material	Plastic
Fitted with:	High-grade steel screws
Knockouts	2 x M20 (cable entry knockouts at the rear) 2 x M20 (cable entry knockouts at the top) 2 x M20/25 (cable entry knockout at the side, 1 x each side)
Number of locations	4
RAL-number	7035
General information	
Degree of protection	NEMA 4X IP67/IP69K
Opening diameter	22.5 mm
Communication	
Connection to SmartWire-DT	No

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Enclosure for control circuit devices (EC000200)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Housing for command and alarm devices (ecl@ss13-27-37-12-05 [AKF023019])

Number of command positions		4
Construction type housing		Surface mounted housing
Housing material		Plastic
Housing material quality		Other
Diameter openings	mm	22.5
Colour housing cover		Grey
Degree of protection (IP)		IP67/IP69K
Degree of protection (NEMA)		4X
Width	mm	186
Height	mm	56
Depth	mm	80