



Fuse-link, high speed, 25 A, AC 1200 V, DC 750 V, 80 kA, 22 × 138 mm, gL/gG, BS



Part no. **25A 1200V AC. 750VDC. BS88 FUSE**  
 Catalog No. **25HD36**

Similar to illustration

### Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	25
Rated voltage			AC 1200 V DC 750 V
Size			22 × 138 mm
Utilization category			gL/gG
Breaking Capacity		kA	80
usable for size/applications			traction
Standard/Approval			BS
Shape			offset bolted tags (slotted)
Standards/Regulations			BS

### Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])			
Construction size			Other
Rated current		A	25
Rated voltage		V	1200
Voltage type			AC/DC
Rated switching capacity		kA	80
Utilization category			gL/gG (cable protection/equipment protection)
Type of fuse status indicator			None
Insulated metal gripping lugs (IMGL)			No