



**Fuse-link, low voltage, 125 A, AC 500 V, 50 kA, D5, 56 x 46 mm, gR, DIN, IEC, fast-acting**

**Part no. FUSE 125A DV 500V TYPE DZ**  
**Catalog No. 125D200Q**

**EL-Nummer 1601258**  
**(Norway)**

**Delivery program**

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	125
Rated voltage			AC 500 V
Construction size			D5
Size			56 x 46 mm
Utilization category			gR
Breaking Capacity		kA	50
usable for size/applications			for fuse-base R2
Release characteristic	class		fast-acting
Standard/Approval			DIN IEC
Shape			bottle
Standards/Regulations			IEC 60269-3 VDE 0636

**Technical data ETIM 7.0**

Circuit breakers and fuses (EG000020) / D-system fuse link (EC000099)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Diazed fuse link (ecl@ss10.0.1-27-14-20-04 [AFZ799015])			
Construction size			DV
Rated current		A	125
Rated voltage		V	500
Colour code			Yellow
Utilization category			gR (general purpose semiconductor protection)
Release characteristic			Fast (F)