

Signalling switch ON-OFF, 2W



**Part no.** IZMX-AS22-40-1  
**184115**  
**EL Number** 4398478  
**(Norway)**

General specifications		
Product name		Eaton Moeller series IZMX/INX auxiliary contact block
Part no.		IZMX-AS22-40-1
EAN		4015081783182
Product Length/Depth		100 millimetre
Product height		100 millimetre
Product width		100 millimetre
Product weight		0.068 kilogram
Compliances		RoHS conform
Product Tradename		IZMX/INX
Product Type		Accessories
Product Sub Type		Auxiliary contact block
Delivery program		
Type		Accessory
Model		Integrable
Special features		2 changeover contacts Retrofit kit for IZMX40 circuit-breakers The retrofit kit includes the required SEC control cable terminals. The basic device already contains two changeover contacts. Mounting kit with 2 additional changeover contacts with cable lengths for IZMX40.
Used with		IZMX40... INX40...
Technical Data - Electrical		
Rated operational current (Ie) at AC-15, 220 V, 230 V, 240 V		10 A
Rated breaking capacity (inductive load)		10 A (250 V AC) 0.25 A (250 V DC) 0.5 A (125 V DC)
Electric connection type		Flat plug-in connection
Technical Data - Mechanical		
Mounting Method		Other
Number of contacts (change-over contacts)		2
Number of contacts (normally closed contacts)		0
Number of contacts (normally open contacts)		0
Number of switches (fault signal)		0
Lamp holder		None
Design verification as per IEC/EN 61439 - technical data		
Ambient operating temperature - min		-25 °C
Ambient operating temperature - max		70 °C
Additional information		
Accessory/spare part type		Auxiliary contact

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Auxiliary contact block (EC000041)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Auxiliary switch block (ecl@ss13-27-37-13-02 [AKN342018])		
Number of contacts as change-over contact		2
Number of contacts as normally open contact		0
Number of contacts as normally closed contact		0
Number of fault-signal switches		0
Rated operation current Ie at AC-15, 230 V	A	10

Type of electric connection			Flat plug-in connection
Model			Integrable
Mounting method			Other
Lamp holder			None