



Fuse-link, low voltage, 45 A, AC 240 V, BS1361, 17 x 35 mm, BS, bulk pack



Powering Business Worldwide™

Catalog No. **BK/C4545**

Similar to illustration

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	45
Rated voltage			AC 240 V
Construction size			BS1361
Size			17 x 35 mm
Description			100 bulk pack
Breaking Capacity		kA	16.5
usable for size/applications			consumer unit
Standard/Approval			BS
Shape			cylindrical
Material			Ceramic body
Standards/Regulations			BS1361

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) (ecl@ss10.0.1-27-14-20-02 [AFZ797013])			
Size			Other
Rated voltage		V	240 - 240
Rated voltage			Other
Voltage type			AC
Utilization category			gL/gG (cable protection/equipment protection)
Rated operating frequency		Hz	45 - 62
Nominal current		A	45
With striker			No
Release characteristic			Other
Breaking capacity		kA	16.5