

F3A-2K - Flange plate 2-component-plastic, up to IP66, metrical entries

Part no. **F3A-2K-M20/16**
EP-501500
 EL Number **2456476**
 (Norway)

General specifications		
Product name		Eaton xEnergy Basic LV systems Low voltage switchgear
Part no.		F3A-2K-M20/16
EAN		9010653053200
Product Length/Depth		140 millimetre
Product height		17.5 millimetre
Product width		230 millimetre
Product weight		0.2 kilogram
Compliances		RoHS conform
Product Tradename		xEnergy Basic
Product Type		LV systems
Product Sub Type		Low voltage switchgear
Delivery program		
Type		Accessory xEnergy series Accessory CS Accessory exterior fitting
Model		Cable screw gland
Accessory/spare part type		Flanges
Technical Data - Mechanical		
Shape		Straight
Surface finishing		RAL 7035, light gray
Surface protection		Untreated
Material		Plastic
Degree of protection		IP66 Other
Number of connector holes		37
Thickness		4 mm
Thread type		Metric
Suitable for nominal thread (PG) - min		16
Suitable for nominal thread (PG) - max		20
Additional information		
Features		Pre-stamping
Special features		Blind flange with knock-outs, RAL 7035, compound of polyamide (PA) and thermoplastic elastomer (TPE)
Used with		Accessory CS Accessory exterior fitting

Technical data ETIM 9.0

Distribution boards (EG000023) / Gland plate for enclosure/cabinet (EC000211)

Electric engineering, automation, process control engineering / Electrical installation, device / Electrical distribution system (including small distribution board) / Gland plate for small distribution boards/switchgear cabinets (ec1@ss13-27-14-24-21 [ADI315012])

Model		Cable screw gland
Type		Straight
Width	mm	230
Height	mm	17.5
Thickness	mm	4
Material		Plastic
Surface protection		Untreated
Degree of protection (NEMA)		Other
Pre-stamping		Yes

Number of connector holes		37
Suitable for cable diameter	mm	0 - 0
Thread type		Metric
Suitable for nominal thread metric/PG		16 - 20
Gland plate type according to SEN 280901		