



Air fuse-link, medium voltage, 63 A, AC 12 kV, 40 kA, BS TA3, 461 x 50.8 mm, back-up, BS, with striker

Part no. 12KV 63AMP 2" AIR FUSE
Catalog No. 12BDGHC63

Similar to illustration

Delivery program

| | | | |
|------------------------------|---|----|---|
| Product range | | | Fuse |
| Basic function | | | Air fuse-link |
| Field of application | | | medium voltage |
| Rated current | I | A | 63 |
| Rated voltage | | | AC 12 kV |
| Construction size | | | BS TA3 |
| Size | | | 461 x 50.8 mm |
| Utilization category | | | back-up |
| Status indicator | | | with striker |
| Breaking Capacity | | kA | 40 |
| usable for size/applications | | | protection of primary side transformers used in fuse switch combination units, fuse bases and fuse switches |
| Standard/Approval | | | BS |
| Shape | | | cylindrical offset bolted tags |
| Standards/Regulations | | | BS2962-1 |

Technical data ETIM 7.0

| | | | |
|--|--|----|-------------------------------------|
| Circuit breakers and fuses (EG000020) / Medium-/high voltage fuse (EC003507) | | | |
| Rated current | | A | 63 |
| Rated voltage | | kV | 12 |
| Voltage type | | | AC |
| Rated frequency | | Hz | 50 - 50 |
| Breaking capacity | | kA | 40 |
| Utilization category | | | Other |
| Application | | | Primary side transformer protection |
| Length | | mm | 461 |
| Diameter | | mm | 51 |
| Performance category according to IEC 60282-1 | | | Back-up |
| With striker | | | Yes |
| Standard | | | British Standard |
| Release characteristic | | | Other |
| Installation technique | | | Air |

Additional product information (links)

| | |
|-------------------------|---|
| Product datasheet (pdf) | http://www1.cooperbusmann.com/pdf/4c55bf59-424e-4973-bb95-bd162228cca8.pdf |
|-------------------------|---|