



Oil fuse-link, medium voltage, 50 A, AC 12 kV, 40 kA, BS2692 F01, 254 x 63.5 mm, back-up, BS, IEC, ESI, with striker, oil-tight

Part no. 12KV 50AMP 2.5" OIL FUSE
Catalog No. 120EFMA50

Similar to illustration

Delivery program

| | | | |
|------------------------------|---|----|---|
| Product range | | | Fuse |
| Basic function | | | Oil fuse-link |
| Field of application | | | medium voltage |
| Rated current | I | A | 50 |
| Rated voltage | | | AC 12 kV |
| Construction size | | | BS2692 F01 |
| Size | | | 254 x 63.5 mm |
| Utilization category | | | back-up |
| Status indicator | | | with striker |
| Description | | | oil-tight |
| Breaking Capacity | | kA | 40 |
| usable for size/applications | | | protection of primary side transformer, and oil-filled fuse switch combination unit |
| Standard/Approval | | | BS IEC ESI |
| Shape | | | cylindrical |
| Standards/Regulations | | | BS2692-1 IEC 60282-1 ESI 12-8 |

Technical data ETIM 7.0

| | | | |
|--|--|----|-------------------------------------|
| Circuit breakers and fuses (EG000020) / Medium-/high voltage fuse (EC003507) | | | |
| Rated current | | A | 50 |
| Rated voltage | | kV | 12 |
| Voltage type | | | AC |
| Rated frequency | | Hz | 50 - 50 |
| Breaking capacity | | kA | 40 |
| Utilization category | | | Other |
| Application | | | Primary side transformer protection |
| Length | | mm | 254 |
| Diameter | | mm | 63.5 |
| Performance category according to IEC 60282-1 | | | Back-up |
| With striker | | | Yes |
| Standard | | | British Standard |
| Release characteristic | | | Other |
| Installation technique | | | Oil |

Additional product information (links)

| | |
|-------------------------|---|
| Product datasheet (pdf) | http://www1.cooperbusmann.com/pdf/4c55bf59-424e-4973-bb95-bd162228cca8.pdf |
|-------------------------|---|