



Expulsion fuse-link, medium voltage, 15 A, AC 15 kV, 8 kA, 533 mm, ANSI, fixed NEMA button head link, T slow



Part no. 15KV 15A EXPULSION LINK
Catalog No. 15TB15

Similar to illustration

Delivery program

| | | | |
|------------------------------|-------|----|--|
| Product range | | | Fuse |
| Basic function | | | Expulsion fuse-link |
| Field of application | | | medium voltage |
| Rated current | I | A | 15 |
| Rated voltage | | | AC 15 kV |
| Size | | | 533 mm |
| Description | | | fixed NEMA button head link |
| Breaking Capacity | | kA | 8 |
| usable for size/applications | | | protection of transformer primary side, feeder, capacitor bank |
| Release characteristic | class | | T slow |
| Standard/Approval | | | ANSI |
| Standards/Regulations | | | ANSI C37-42 |

Technical data ETIM 7.0

| | | | |
|--|--|----|------------------|
| Circuit breakers and fuses (EG000020) / Expulsion fuse-link, medium voltage (EC003611) | | | |
| Rated current | | A | 15 |
| Rated voltage | | V | 15000 |
| Voltage type | | | AC |
| Rated frequency | | Hz | 45 - 62 |
| Release characteristic | | | T |
| Type of termination | | | Fixed buttonhead |
| Standard | | | ANSI |

Additional product information (links)

| | |
|-------------------------|---|
| Product datasheet (pdf) | http://www1.cooperbusmann.com/pdf/4c55bf59-424e-4973-bb95-bd162228cca8.pdf |
|-------------------------|---|