



Reset remote, 24VDC

Part no. IZMX-RR24DC-40-1  
 Catalog No. 184125  
 Alternate Catalog No. 68D2806G63  
 EL-Nummer (Norway) 0004398488

### Delivery program

Product range		Accessories
Accessories		Trip indication / Reset options
Accessories		Remote reset
		The circuit-breaker is equipped with a mechanical trip indicator (red pin). After the remote reset coil is electrically actuated, the reclosing lockout can be reset. Cannot be combined with remote reset.
Rated control voltage	U <sub>s</sub> V	24 V DC
For use with		IZMX40...W IZMX40...F
Instructions		The retrofit kit includes the required SEC control cable terminals.

### Design verification as per IEC/EN 61439

Technical data for design verification		
Operating ambient temperature min.	°C	-25
Operating ambient temperature max.	°C	70

### Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Shunt release (for power circuit breaker) (EC001023)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Full load current trip (ecl@ss10.0.1-27-37-04-18 [AKF016013])		
Rated control supply voltage U <sub>s</sub> at AC 50HZ	V	0 - 0
Rated control supply voltage U <sub>s</sub> at AC 60HZ	V	0 - 0
Rated control supply voltage U <sub>s</sub> at DC	V	24 - 24
Voltage type for actuating		DC
Initial value of the undelayed short-circuit release - setting range	A	0
End value adjustment range undelayed short-circuit release	A	0
Type of electric connection		Flat plug-in connection
Number of contacts as normally open contact		0
Number of contacts as normally closed contact		0
Number of contacts as change-over contact		0
Suitable for power circuit breaker		Yes
Suitable for off-load switch		Yes
Suitable for motor safety switch		No
Suitable for overload relay		No