DATASHEET - M22-FI4-*

Surface mounting enclosure, 4 mounting locations, M22, flat

Part no.   **M22-FI4-***
                    197641

EAT·N

Powering Business Worldwide™

General specifications

Product name		Eaton Moeller® series M22 Accessory Surface mounting enclosure
Part no.		M22-FI4-*
Product Length/Depth		279 millimetre
Product height		44 millimetre
Product width		43 millimetre
Product weight		0.201 kilogram
Certifications		CSA File No.: 012528 UL 508 IEC/EN 60947-5 UL Listed UL Category Control No.: NKCR CSA Class No.: 3211-03 CE marking CSA-C22.2 No. 94-91 CSA certified CSA-C22.2 No. 14-05 UL File No.: E29184
Product Tradename		M22
Product Type		Accessory
Product Sub Type		Surface mounting enclosure
Catalog Notes		Individually markable with pushbutton configurator

Features & Functions

Enclosure color		Gray
Enclosure material		Plastic
Fitted with:		High-grade steel screws
Knockouts		1 x M20 (cable entry knockouts at the rear) 2 x M20 (cable entry knockout at the side, 1 x each side)
Number of locations		4
RAL-number		7035

General information

Degree of protection		IP67/IP69K NEMA 4X
Opening diameter		22.5 mm

Communication

Connection to SmartWire-DT		No

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Enclosure for control circuit devices (EC000200)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Housing for command and alarm devices (ecl@ss13-27-37-12-05 [AKF023019])

Number of command positions		4
Construction type housing		Surface mounted housing
Housing material		Plastic
Housing material quality		Other
Diameter openings	mm	22.5
Colour housing cover		Grey
Degree of protection (IP)		IP67/IP69K
Degree of protection (NEMA)		4X
Width	mm	43
Height	mm	44
Depth	mm	279