



Expulsion fuse-link, medium voltage, 50 A, AC 25 kV, 8 kA, 660 mm, ANSI, removable NEMA button head link, T slow



Powering Business Worldwide™

Part no. **25KV 50AMP EXPULSION LINK**
 Catalog No. **25TBR50**

Delivery program

Product range			Fuse
Basic function			Expulsion fuse-link
Field of application			medium voltage
Rated current	I	A	50
Rated voltage			AC 25 kV
Size			660 mm
Description			removable NEMA button head link
Breaking Capacity		kA	8
usable for size/applications			protection of transformer primary side, feeder, capacitor bank
Release characteristic	class		T slow
Standard/Approval			ANSI
Standards/Regulations			ANSI C37-42

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Expulsion fuse-link, medium voltage (EC003611)			
Rated current		A	50
Rated voltage		V	25000
Voltage type			AC
Rated frequency		Hz	45 - 62
Release characteristic			T
Type of termination			Removable buttonhead
Standard			ANSI

Additional product information (links)

Medium voltage full-line catalogue (pdf)	http://www1.cooperbusmann.com/pdf/4c55bf59-424e-4973-bb95-bd162228cca8.pdf
--	---