



Fuse-link, low voltage, 500 A, AC 660 V, BS88, 74 x 112 mm, gL/gG, BS

500R20

Product name		Eaton Bussmann series low voltage British standard fuse
Part no.		500R20
EAN		5027590049542
Product Length/Depth		112 millimetre
Product height		75 millimetre
Product width		75 millimetre
Product weight		932 gram
Compliances		CE Marked RoHS Compliant
Certifications		EAC IEC 60269 BS88
Product Tradename		None
Product Type		Low voltage British standard fuse
Product Sub Type		None
Amperage Rating		500 A
Voltage rating		660 V
Voltage type		AC
Breaking capacity		80 kA
Class		Class gG/gL
Application		general industrial applications
Fuse type		R20
Connection		94 mm fixing centre

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011])		
Fuse construction type according to IEC 60269		Other
Type of current		AC
Rated voltage AC	V	660
Rated voltage DC	V	
Rated current	A	500
Utilization category		gL/gG (cable protection/equipment protection)
Breaking capacity	kA	80
Colour code		None
Type of fuse status indicator		None
Power loss at rated current	W	38
Mounting holes		M8
Centre-to-centre distance of connections	mm	94