



Eaton 9E 6000i

Part no.  
Catalog No.

Eaton 9E 6000i  
9E6KI

### Technical data ETIM 7.0

| Data and telecommunication (EG000037) / UPS (EC000382)   |     |                     |
|--|-----|---------------------|
| Electric engineering, automation, process control engineering / Power supply devices / No-break power supply (complete) / No-break power supply (complete, unspecified)<br>(ec@ss10.0.1-27-04-06-90 [BAB258012]) |     |                     |
| Input voltage  | V   | 110 - 276           |
| Primary frequency  | Hz  | 40 - 70             |
| Number of phases primary   |     | 1                   |
| Output voltage   | V   | 220 - 240           |
| Secondary frequency  | Hz  | 50 - 60             |
| Output effective power   | W   | 4800                |
| Output apparent power  | VA  | 6000                |
| Type of interface  |     | Other               |
| Number of phases secondary   |     | 1                   |
| SNMP   |     | Yes                 |
| Voltage type   |     | AC                  |
| Height   | mm  | 708.5               |
| Width  | mm  | 262.4               |
| Depth  | mm  | 612.9               |
| Transition time for full load  | min | 8                   |
| Weight   | kg  | 68                  |
| Network-management   |     | Yes                 |
| USV- technology  |     | Online              |
| Construction type  |     | Free standing model |
| Max. voltage distortion output (linear load)   | %   | 2                   |
| Output power factor  |     | 0.8                 |
| Overall efficiency   | %   | 91                  |
| Efficiency in eco-mode   | %   | 96                  |
| Potential free switch contact  |     | Yes                 |
| Auto shut down function  |     | Yes                 |
| Input connection   |     | Fixed connection    |
| Number of output connections C13   |     | 0                   |
| Number of output connections C19   |     | 0                   |
| Number of output connections with protective contact (SCHUKO)  |     | 0                   |
| Number of output connections fixed connection  |     | 1                   |