



Eaton Metered Input rack PDU, 2U, Input IEC-60309 32A 1Ph, 7.4 kW max, 32A, 200-240V, Outlets 12XC13 : 4XC19



Catalog No. EMIH06

Similar to illustration

Delivery program

Type			Rack PDU
Input Connection			IEC-60309 32A 1Ph
Cord Length			3m
Input Voltage			200-240V
Phase			Single-phase
Frequency Rating			50/60 Hz
Ethernet Interface			Yes
Serial Interface			Yes
Form Factor			2U
Outlet Control			No
Operating Temperature			0° to 60°C (32° to 140°F)
Outlets			12XC13 : 4XC19
Number of Outputs C13			12
Number of Outputs C19			4
Amperage Rating			32A
Mounting Direction			Horizontal
ETIM Class			EC002762
Fitted With:			Display Ampere Meter Mounting material
Electrical Connection			Connecting cord with plug
Evaluation			At distance
Mounting Dimension (metrical)			444.5
Mounting Dimension (standardised)			482.6 mm (19 inch)
Switchable			No
Over Voltage Category			2
Wattage			7.4 kW max
Communication			HTTP, HTTPS, SSL, Telnet, FTP, SNMP, SMTP, DNS, DHCP, LDAP, RADIUS
SNMP			Yes
Mass Configuration			Yes
Package Contents			PDU mounting accessories network cable configuration cable splitter for daisy-chaining Quickstart Safety Instructions
Number of Outputs C20			0
Num of Outputs PC (SCHUKO)			0
Number of Outputs (Other)			0

Number of Outlets with Earth Pin		16
Circuit Breaker		(2) single-pole
Color		Black

Technical data ETIM 7.0

Domestic switching devices (EG000013) / Power distribution unit (PDU) (EC002762)		
Electric engineering, automation, process control engineering / Electrical installation, device / Low-voltage distribution system (mobile) / Low-voltage distribution systems (mobile, unspecified) (ecl@ss10.0.1-27-14-26-90 [AKN612013])		
Mounting dimension (standardised)		482.6 mm (19 inch)
Mounting dimension	mm	444.5
Mounting direction		Horizontal
Electrical connection		Connecting cord with plug
Type of electric connection		Other
Cable length	m	3
Number of socket outlets with protective contact		0
Number of socket outlets with earth pin		16
Number of C13 socket outlets		12
Number of C19 socket outlets		4
Number of C20 socket outlets		0
Number of UK BS1363 sockets		
number of socket outlets swiss standard type 13		
number of socket outlets swiss standard type 15		
number of socket outlets swiss standard type 23		
number of socket outlets swiss standard type 25		
Number of other socket outlets		0
Number of height units		2
Length	mm	127
Width	mm	87.2
Height	mm	444.5
Depth	mm	127
Supply voltage	V	
Over voltage category		2
Mains filter		No
Switchable		No
SNMP		Yes
With display		Yes
Evaluation		At distance
With LED indication		No
With fuse		No
Ampere meter		Yes
With temperature measurement		No
With mounting material		Yes