## Fuse-link, LV, 630 A, AC 415 V, BS88, $74 \times 262 \text{ mm}$ , gL/gG, BS



## FG630

Product name	Eaton Bussmann series low voltage British standard fuse
Part no.	FG630
EAN	5027590019972
Product Length/Depth	263 millimetre
Product height	74 millimetre
Product width	74 millimetre
Product weight	1275 gram
Compliances	RoHS Compliant
Product Tradename	None
Product Type	Low voltage British standard fuse
Product Sub Type	None
Amperage Rating	630 A
Voltage rating	415 V
Voltage type	AC/DC
Breaking capacity	80 kA
Class	Class gG/gL
Application	general industrial applications
Fuse type	FG
Fitted with:	Centre bolted tags
Connection	167/231 mm fixing centre

## **Technical data ETIM 8.0**

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)						
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011])						
Fuse construction type according to IEC 60269			Other			
Type of current			AC/DC			
Rated voltage AC		V	415			
Rated voltage DC		V	400			
Rated current		Α	630			
Utilization category			gL/gG (cable protection/equipment protection)			
Breaking capacity		kA	80			
Colour code			None			
Type of fuse status indicator			None			
Power loss at rated current		W	50			
Mounting holes			M10			
Centre-to-centre distance of connections		mm	231			