



Fuse-link, high speed, 140 A, AC 690 V, BS88, 20 x 37 x 139 mm, aR, BS

**Part no.** 140A 690V AC TYPE T FUSE (5)  
**Catalog No.** 140CEET

### Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	140
Rated voltage			AC 690 V
Construction size			BS88
Size			20 x 37 x 139 mm
Utilization category			aR
Description			110 mm fixing centres
Breaking Capacity		kA	200
usable for size/applications			protection of DC common bus, DC drives, power converters/rectifiers and reduced voltage starters
Standard/Approval			BS
Shape			offset bolted tags (slotted), dual barrel
Standards/Regulations			BS88-4 IEC 60269-4
Optional accessories			fuse-block BH-1132

### Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])			
Construction size			Other
Rated current		A	140
Rated voltage		V	690
Voltage type			AC
Rated switching capacity		kA	200
Utilization category			aR (accompanied semiconductor protection)
Type of fuse status indicator			None
Insulated metal gripping lugs (IMGL)			No

### Additional product information (links)

Product datasheet (pdf)	<a href="http://www1.cooperbusssmann.com/pdf/4a317260-8e98-40d9-b43b-e80c53a102f6.pdf">http://www1.cooperbusssmann.com/pdf/4a317260-8e98-40d9-b43b-e80c53a102f6.pdf</a>
-------------------------	---