



**Door coupling handle, for Modan, 90 degree, Twisted**

**Part no.** PKE32-XHT-M  
**Catalog No.** 173424  
**Alternate Catalog No.** XTPE032XRHMTMODB

**Delivery program**

Product range		Accessories
Accessories		Door coupling handle
		For use as a main switch to EN 60204 in MCC power distribution systems and with PKE installed when rotated by 90°
		Black
For use with		Door coupling handle PKE
Degree of Protection		IP65

**Notes** Plug-in extension shaft PKZ0-XAH can be cut to desired length for mounting depths of 100-240 mm.  
 Carrier with extension shaft included as standard.  
 With ON/OFF switch position and "+" (tripped), lockable.  
 With 3 padlocks, 4 - 8 mm hasp thickness.  
 Cannot be used in combination with VHI20-PKZ0.  
 ZFS... (except for ZFS-(L)TS-NZM) add-on front plates can be used.

**Technical data ETIM 7.0**

Low-voltage industrial components (EG000017) / Door coupling handle for switchgear (EC000230)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Hand drive for switch devices (ecl@ss10.0.1-27-37-04-15 [AKF013014])		
With axis extension		Yes
With door interlock		Yes
Lockable		Yes
With handle red/yellow		No

**Additional product information (links)**

Motor starters and "Special Purpose Ratings" for the North American market	<a href="http://www.eaton.eu/ecm/groups/public/@pub/@europe/@electrical/documents/content/pct_3258146.pdf">http://www.eaton.eu/ecm/groups/public/@pub/@europe/@electrical/documents/content/pct_3258146.pdf</a>
Busbar Component Adapters for modern Industrial control panels	<a href="http://www.moeller.net/binary/ver_techpapers/ver960en.pdf">http://www.moeller.net/binary/ver_techpapers/ver960en.pdf</a>