

Changeover switch, RMQ-Titan, with thumb-grip, maintained, 3 positions,
Front ring stainless steel



Powering Business Worldwide™

Part no. **M30I-FWRK3**
188187

Product name	Eaton Moeller® series M30 Changeover switch
Part no.	M30I-FWRK3
EAN	4015081858484
Product Length/Depth	36 millimetre
Product height	47 millimetre
Product width	46 millimetre
Product weight	0.042 kilogram
Certifications	IEC/EN 60947 VDE 0660 CSA-C22.2 No. 94-91 IEC/EN 60947-5 DNV CSA Class No.: 3211-03 UL Category Control No.: NKCR CSA file No. 012528 GL CSA-C22.2 No. 14-05 UL 508 UL Listed CSA certified UL File No.: E29184 CE marking
Product Tradename	M30
Product Type	Changeover switch
Product Sub Type	None
Bezel color	Stainless steel
Bezel material	Metal
Design	With thumb-grip Flat front
Fitted with:	Plunger bridge for the middle contact Front ring
Functions	Stay-put/spring-return function, can be changed with coding parts M22-XC-Y
Degree of protection	NEMA 4X, 13
Degree of protection (front side)	IP66
Lifespan, mechanical	100,000 Operations
Opening diameter	30 mm
Operating frequency	2000 Operations/h
Operating torque	0.3 N·m
Product category	RMQ-Titan
Size	Front dimensions: Ø 36 mm
Switching angle	60 °
Type	Selector switch actuator
Mounting position	As required
Shock resistance	15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Mechanical, According to IEC/EN 60068-2-27
Ambient operating temperature - min	-25 °C
Ambient operating temperature - max	70 °C
Ambient storage temperature - min	40 °C
Ambient storage temperature - max	80 °C
Climatic proofing	Damp heat, cyclic, to IEC 60068-2-30

		Damp heat, constant, to IEC 60068-2-78
Connection to SmartWire-DT		With SWD-RMQ connections Yes
Actuator color		Black
Actuator function		Maintained Switching function latching
Actuator type		Toggle
Number of switch positions		3
Force for positive opening - min		0 N

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Front element for selector switch (EC000222)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Front element for selector switches (ecl@ss10.0.1-27-37-12-13 [AKF031014])		
Number of switch positions		3
Type of control element		Toggle
Suitable for illumination		No
Colour control element		Black
Colour indicator light cap		Other
Construction type lens		Round
Hole diameter	mm	30
Width opening	mm	0
Height opening	mm	0
Switching function latching		Yes
Spring-return		No
With front ring		Yes
Material front ring		Metal
Colour front ring		Stainless steel
Degree of protection (IP), front side		IP66
Degree of protection (NEMA)		4X, 13