

**Illuminated selector switch actuator, RMQ-Titan, with thumb-grip,  
momentary, 2 positions, green, Front ring stainless steel**

**Part no. M30I-FWLK-G  
188198**

Product name	Eaton Moeller® series M30 Illuminated selector switch actuator
Part no.	M30I-FWLK-G
EAN	4015081858583
Product Length/Depth	36 millimetre
Product height	47 millimetre
Product width	46 millimetre
Product weight	0.042 kilogram
Certifications	IEC/EN 60947 VDE 0660 UL Listed CSA Class No.: 3211-03 UL Category Control No.: NKCR CSA file No. 012528 CE marking CSA-C22.2 No. 14-05 CSA-C22.2 No. 94-91 CSA certified IEC/EN 60947-5 UL 508 DNV UL File No.: E29184 GL
Product Tradename	M30
Product Type	Illuminated selector switch actuator
Product Sub Type	None
Bezel color	Stainless steel
Bezel material	Metal
Design	With thumb-grip Flat front
Fitted with:	Front ring
Functions	Stay-put/spring-return function, can be changed with coding parts M22-XC-Y
Degree of protection	NEMA 4X, 13
Degree of protection (front side)	IP66
Lifespan, mechanical	100,000 Operations
Opening diameter	30 mm
Operating frequency	2000 Operations/h
Operating torque	0.3 N-m
Product category	RMQ-Titan
Size	Front dimensions: Ø 36 mm
Suitable for	Illumination
Switching angle	40 °
Type	Illuminated selector switch actuator
Mounting position	As required
Shock resistance	15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Mechanical, According to IEC/EN 60068-2-27
Ambient operating temperature - min	-25 °C
Ambient operating temperature - max	70 °C
Climatic proofing	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30

Connection to SmartWire-DT			With SWD-RMQ connections Yes
Actuator color			Green
Actuator function			Spring-return Momentary
Actuator type			Toggle
Number of switch positions			2
Force for positive opening - min			0 N

## Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Front element for selector switch (EC000222)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Front element for selector switches (ecl@ss10.0.1-27-37-12-13 [AKF031014])			
Number of switch positions			2
Type of control element			Toggle
Suitable for illumination			Yes
Colour control element			Green
Colour indicator light cap			Green
Construction type lens			Round
Hole diameter		mm	30
Width opening		mm	0
Height opening		mm	0
Switching function latching			No
Spring-return			Yes
With front ring			Yes
Material front ring			Metal
Colour front ring			Stainless steel
Degree of protection (IP), front side			IP66
Degree of protection (NEMA)			4X, 13