



Low voltage NH fuse

224NHG1BI-690

Product name	Eaton Bussmann series low voltage NH Fuse
Part no.	NH FUSE 224A 690V AC gG 1 DUAL IND
EAN	5027590468626
Product Length/Depth	135 millimetre
Product height	63 millimetre
Product width	40 millimetre
Product weight	407.333333 gram
Compliances	RoHS Compliant CE Marked
Certifications	IEC 60269-1 DIN 43620 IEC 60269-2
Product Tradename	None
Product Type	Low voltage NH fuse
Product Sub Type	None
Amperage Rating	224 A
Voltage rating	690 V
Voltage type	AC
Breaking capacity	120 kA
Class	Class gG/gL
Fuse size	NH1
Insulated metal gripping lugs (IMGL)	Yes
Suitable for	SD1-D Single pole NH Fuse base TD1-D Tripe pole NH Fuse base Microswitch 170H0236 EBH Size 00 to 4 Horizontal fuse switch-disconnectors

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / Knife blade fuse (EC000055)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])		
Fuse construction type according to IEC 60269		NH1
Voltage type		AC
Rated current	A	224
Rated voltage AC	V	690
Rated voltage DC	V	
Rated switching capacity	kA	120
Utilization category		gL/gG (cable protection/equipment protection)
Type of fuse status indicator		Combination fuse status indicator
Insulated metal gripping lugs (IMGL)		Yes
Power loss at rated current	W	19