

Switch-disconnector, 3p, 2500A, withdrawable part



**Part no.** **IN32N3-25W-1**  
**EP-500136**

Product name	Eaton IZM32/IN32 switch-disconnector
Part no.	IN32N3-25W-1
EAN	9010653016991
Product Length/Depth	511 millimetre
Product height	514 millimetre
Product width	492 millimetre
Product weight	86.925 kilogram
Compliances	RoHS conform
Certifications	CE
Product Tradename	IZM32/IN32
Product Type	Switch-disconnector
Product Sub Type	None
Actuator color	Green
Actuator type	Push button
Degree of protection (front side)	IP20
Device construction	Built-in device slide-in technique (withdrawable)
Electrical connection type of main circuit	Rail connection
Features	Motor drive optional Version as main switch
Functions	Interlockable Voltage release optional
Number of auxiliary contacts (change-over contacts)	4
Number of auxiliary contacts (normally closed contacts)	0
Number of auxiliary contacts (normally open contacts)	0
Number of poles	Three-pole
Position of connection for main current circuit	Back side
Rated operating power at AC-23, 400 V	0 kW
Rated operating power at AC-3, 400 V	0 kW
Rated operating voltage (Ue) - min	440 V
Rated operating voltage (Ue) at AC - max	690 V
Rated permanent current at AC-21, 400 V	2500 A
Rated permanent current at AC-23, 400 V	2500 A
Rated short-time withstand current (Icw)	85 kA
Rated uninterrupted current (Iu)	2500 A
Suitable for	Distribution board installation Floor mounting
Switching power at 400 V	0 kW