

## UNITRONIC® BUS HEAT 6722

CAN bus cable for utility vehicles

CAN bus cable for use in utility vehicles with extended requirements, like higher temperature range, resistance against UV, operating fluids etc.

### Info

Designed according to ISO 6722  
tested acc.to ECE-R 118.01



### ENopen

-  Supplementary automation components from Lapp
-  e-Mobility
-  Suitable for outdoor use
-  Good chemical resistance
-  Flame-retardant
-  Halogen-free
-  Space requirement
-  Temperature-resistant
-  UV-resistant

Last Update (26.02.2021)

©2021 Lapp Group - Technical changes reserved

Product Management [www.lappkabel.de](http://www.lappkabel.de)

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02\_03.16

## UNITRONIC® BUS HEAT 6722

### Benefits

Star-quad stranding, thus less space requirement and weight  
Extended temperature range  
Good resistance to oil, petrol, acids and alkalis

### Application range

Suitable for connecting to of e.g. camera systems, enter-/ infotainment for passengers, ticketing systems  
For fixed, occasionally flexible and protected use inside of utility vehicles

### Product features

Halogen-free outer sheath  
Maximum bit rate: 1 Mbit/s for 40 m segment length  
temperature class B on the basis of ISO 6722-1  
ISO 11898 makes recommendations for the segment length, cable cross section and bit rate  
Flame-retardant according IEC 60332-1-2

### Norm references / Approvals

Standardised internationally in ISO 11898

### Product Make-up

Stranded bare conductor  
PUR outer sheath  
Colour: black  
UV-resistant (but colour may change after some time)  
Screening: wrapped with braided copper wires

### Technical Data

Classification ETIM 6:	ETIM 6.0 Class-ID: EC000830 ETIM 6.0 Class-Description: Data cable
Mutual capacitance:	40 nF/km (800 Hz)
Peak operating voltage:	250 V (not for power transmission)
Conductor resistance:	(loop): max. 159.8 ohm/km
Minimum bending radius:	Flexing: 15 x outer diameter
Test voltage:	Core/core: 1500 V rms
Characteristic impedance:	120 ohm
Temperature range:	Fixed installation: -40 °C to +105 °C occasionally flexing: -30 °C to +105 °C

### Note

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.

Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.

Please find our standard lengths at: [www.lappkabel.de/en/cable-standardlengths](http://www.lappkabel.de/en/cable-standardlengths)

Packaging size: coil  $\leq$  30 kg or  $\leq$  250 m, otherwise drum

Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

Prices are net prices without VAT and surcharges. Sale to business customers only.

Last Update (26.02.2021)

©2021 Lapp Group - Technical changes reserved

Product Management [www.lappkabel.de](http://www.lappkabel.de)

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02\_03.16

**UNITRONIC® BUS HEAT 6722**

Article number	Article designation	Number of cores and mm <sup>2</sup> per conductor	Outer diameter [mm]	Copper index [kg/km]	Weight [kg/km]
2170385	UNITRONIC® BUS HEAT 6722	1 x 4 x 0.25	6.45	26	46
2170386	UNITRONIC® BUS HEAT 6722	1 x 4 x 0.34	7.54	33	61
2170387	UNITRONIC® BUS HEAT 6722	1 x 4 x 0.5	8.36	41	70
2170388	UNITRONIC® BUS HEAT 6722	1 x 4 x 0.75	9.79	59	95

Last Update (26.02.2021)

©2021 Lapp Group - Technical changes reserved

Product Management [www.lappkabel.de](http://www.lappkabel.de)You can find the current technical data in the corresponding data sheet.  
PN 0456 / 02\_03.16