

## SKINTOP® CLICK BS

SKINTOP® CLICK BS, bending protection with innovative CLICK system to protect flexible cables, no thread required, no counter nut

### Info

The most innovative cable insertion system in the market for a fast and highly flexible assembly. Simply click in - turn to the left - turn to the right - finished. The result: fixed, centred, strain-relieved fitting and maximum protection class in a few seconds.



-  Good chemical resistance
-  Heat-resistant
-  Mechanical resistance
-  Assembly time
-  Space requirement
-  Acid-resistant
-  Variety of approval certifications

### Benefits

Reliable bending protection for cable conservation and functional reliability

Save up to 70% of the time with the innovative CLICK system

No thread required

To protect flexible cables

Fewer parts, counter nut no longer needed

Last Update (01.03.2022)

©2022 Lapp Group - Technical changes reserved

Product Management [www.lappkabel.de](http://www.lappkabel.de)

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02\_03.16

## SKINTOP® CLICK BS

### Application range

Cables for electrical appliances and machinery that are moved under normal use must be protected against excessive bending as required in accordance with VDE 0700-1

Robotics industry  
Moving machine parts  
Apparatus construction  
Light and sound applications

### Norm references / Approvals

UL File Nr. E79903

### Included

Included: disassembly tool

### Technical Data

|                        |   |
|------------------------|---|
| Classification ETIM 5: | ETIM 5.0 Class-ID: EC000441<br>ETIM 5.0 Class-Description: Cable screw gland      |
| Classification ETIM 6: | ETIM 6.0 Class-ID: EC000441<br>ETIM 6.0 Class-Description: Cable screw gland      |
| Colour delivered:      | Silver grey (RAL 7001)<br>Light grey (RAL 7035)<br>Black (RAL 9005), UV-resistant |
| Material:              | Body: special polyamide<br>Seal: special elastomer                                |
| Protection rating:     | IP 68 - 4 bar (M12)<br>IP 68 - 5 bar (M16 - M25)<br>IP 68 - 1 bar (M32)           |
| Temperature range:     | -20°C to +100°C   |

### Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products. Prices are net prices without VAT and surcharges. Sale to business customers only.

**SKINTOP® CLICK BS**

| Article number                       | Article designation / size | Ø F mm  | M (hole in mm) | SW1/SW2 mm  | Overall length C mm | Thread length D mm | Wall thickness, S (mm) | Pieces / PU |
|--------------------------------------|----------------------------|---------|----------------|-------------|---------------------|--------------------|------------------------|-------------|
| <b>SKINTOP® CLICK BS light grey</b>  |                            |         |                |             |                     |                    |                        |             |
| 53112932                             | CLICK BS 12                | 3.5 - 7 | 12.3 (-0.2)    | 18.0 / 15.0 | 74.0                | 8                  | 1.0 - 4.0              | 50          |
| 53112888                             | CLICK BS 16                | 5 - 9   | 16.3 (-0.2)    | 22.0 / 19.0 | 94.0                | 8                  | 1.0 - 4.0              | 50          |
| 53112889                             | CLICK BS 20                | 7 - 13  | 20.3 (-0.2)    | 27.0 / 25.0 | 108.0               | 8                  | 1.0 - 4.0              | 25          |
| 53112890                             | CLICK BS 25                | 9 - 17  | 25.3 (-0.2)    | 32.0 / 30.0 | 127.0               | 8                  | 1.0 - 4.0              | 25          |
| 53112933                             | CLICK BS 32                | 11 - 20 | 32.3 (-0.2)    | 40.0 / 36.0 | 156.0               | 8                  | 1.0 - 4.0              | 25          |
| <b>SKINTOP® CLICK BS silver grey</b> |                            |         |                |             |                     |                    |                        |             |
| 53112934                             | CLICK BS 12                | 3.5 - 7 | 12.3 (-0.2)    | 18.0 / 15.0 | 74.0                | 8                  | 1.0 - 4.0              | 50          |
| 53112906                             | CLICK BS 16                | 5 - 9   | 16.3 (-0.2)    | 22.0 / 25.0 | 94.0                | 8                  | 1.0 - 4.0              | 50          |
| 53112907                             | CLICK BS 20                | 7 - 13  | 20.3 (-0.2)    | 27.0 / 25.0 | 108.0               | 8                  | 1.0 - 4.0              | 25          |
| 53112908                             | CLICK BS 25                | 9 - 17  | 25.3 (-0.2)    | 32.0 / 30.0 | 127.0               | 8                  | 1.0 - 4.0              | 25          |
| 53112935                             | CLICK BS 32                | 11 - 20 | 32.3 (-0.2)    | 40.0 / 36.0 | 156.0               | 8                  | 1.0 - 4.0              | 25          |
| <b>SKINTOP® CLICK BS black</b>       |                            |         |                |             |                     |                    |                        |             |
| 53112936                             | CLICK BS 12                | 3.5 - 7 | 12.3 (-0.2)    | 18.0 / 15.0 | 74.0                | 8                  | 1.0 - 4.0              | 50          |
| 53112909                             | CLICK BS 16                | 5 - 9   | 16.3 (-0.2)    | 22.0 / 19.0 | 94.0                | 8                  | 1.0 - 4.0              | 50          |
| 53112911                             | CLICK BS 20                | 7 - 13  | 20.3 (-0.2)    | 27.0 / 25.0 | 108.0               | 8                  | 1.0 - 4.0              | 25          |
| 53112912                             | CLICK BS 25                | 9 - 17  | 25.3 (-0.2)    | 32.0 / 30.0 | 127.0               | 8                  | 1.0 - 4.0              | 25          |
| 53112937                             | CLICK BS 32                | 11 - 20 | 32.3 (-0.2)    | 40.0 / 36.0 | 156.0               | 8                  | 1.0 - 4.0              | 25          |

Last Update (01.03.2022)

©2022 Lapp Group - Technical changes reserved

 Product Management [www.lappkabel.de](http://www.lappkabel.de)

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02\_03\_16

## SKINTOP® CLICK BS

