

SILVYN® MSK-M ATEX BRUSH

SILVYN® MSK-M ATEX BRUSH - nickel-plated brass conduit fitting for ATEX environment, integrated cable strain relief

Info

IECEx approval worldwide

Optimum 360° screen contact



Wide clamping range



Mechanical resistance



Assembly time



Optimum strain relief



Robust



Reliability



Integrated SKINTOP[®] cable gland



Interference signals

Benefits

Easy installation

Faster, easier screen contact

Optimum cable and conduit strain relief

Last Update (04.02.2022)

©2022 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

SILVYN® MSK-M ATEX BRUSH

Maximum cable sealing
Wide clamping range

Application range

Devices, machines and apparatus of enhanced safety protection type "e", dust ignition proof "t"
Chemical and petrochemical industry
Plant engineering
Used in areas where cables and wires need additional mechanical protection

Product features

Combination of SILVYN® and SKINTOP®

Product Make-up

SILVYN® conduit connection via inner sleeve and cap nut
Metric connection thread acc. to DIN EN 60423

Note

To be used in Ex environment only in combination with metal conduits without a plastic jacket

Technical Data

| | |
|------------------------|--|
| Classification ETIM 5: | ETIM 5.0 Class-ID: EC001180 ETIM 5.0 Class-Description: Screw connection for protective metallic hose |
| Classification ETIM 6: | ETIM 6.0 Class-ID: EC001180 ETIM 6.0 Class-Description: Screw connection for protective metallic hose |
| Certifications: | CE 0637 Ex II 2G Ex eb IIC Ex II 1D Ex ta IIIC IECEX IBE 13.0033X |
| Material: | Basis type: Body: nickel-plated brass Conduit connector seal: CR/NBR Tube seal: TPE EMC brush: brass |
| Tests: | DIN EN 60079-0 DIN EN 60079-7 DIN EN 60079-31 |
| Protection rating: | Cable: IP 68 Conduit: IP 40 with SILVYN® AS, EDU-AS, EMC AS-CU |
| Temperature range: | -30 °C to +90 °C |

Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products.
Prices are net prices without VAT and surcharges. Sale to business customers only.

SILVYN® MSK-M ATEX BRUSH

| Article number | Metric size | Clamping range in mm | Clear opening (mm) | Suitable for conduit Ø (mm) | Pieces / PU |
|---|-------------|----------------------|--------------------|-----------------------------|-------------|
| SILVYN® MSK-M ATEX BRUSH for SILVYN® AS | | | | | |
| 55506042 | 25 x 1.5 | 9.0 - 17.0 | 14.5 | 21 | 10 |
| 55506043 | 32 x 1.5 | 11.0 - 21.0 | 19.5 | 27 | 1 |
| 55506044 | 40 x 1.5 | 19.0 - 28.0 | 26.5 | 36 | 1 |
| 55506045 | 50 x 1.5 | 27.0 - 35.0 | 36 | 45 | 1 |
| 55506030 | 63 x 1.5 | 34.0 - 45.0 | 45.5 | 56 | 1 |
| SILVYN® MSK-M ATEX BRUSH for SILVYN® EDU-AS / EMC AS-CU | | | | | |
| 55506031 | 25 x 1.5 | 9.0 - 17.0 | 14.5 | 21 | 10 |
| 55506032 | 32 x 1.5 | 11.0 - 21.0 | 19.5 | 27 | 1 |
| 55506033 | 40 x 1.5 | 19.0 - 28.0 | 26.5 | 36 | 1 |
| 55506034 | 50 x 1.5 | 27.0 - 35.0 | 36 | 45 | 1 |
| 55506035 | 63 x 1.5 | 34.0 - 45.0 | 45.5 | 56 | 1 |

Last Update (04.02.2022)

©2022 Lapp Group - Technical changes reserved

Product Management www.lappkabel.deYou can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03_16