

# SILVYN® TC

SILVYN® TC is a parallel corrugated conduit with an innovative design due to integrated metric threads, mountable with standard metric counter nut

#### Info

No conduit gland required With counter nut usable Selected section length





Good chemical resistance



Halogen-free



Assembly time



Low weight



**UV-resistant** 

### **Benefits**

Dimensionally stable
Flexible
Threaded
Cost-saving due to quick and easy installation

## **Application range**

Control cabinet manufacturing Mechanical engineering Plant engineering For indoor and outdoor use

# **Product features**

Halogen and cadmium-free Abrasion-resistant

Last Update (11.01.2022)
©2022 Lapp Group - Technical changes reserved
Product Management www.lappkabel.de
You can find the current technical data in the corresponding data sheet.
PN 0456 / 02\_03.16



# SILVYN® TC

High resistance to oil, petrol, acids and other chemicals

#### **Product Make-up**

Fine-profile corrugated polyamide 6 conduit

#### Note

We recommend to use an additional sealing to maximize the IP rating Section length 222  $\mbox{\sc mm}$ 

### **Technical Data**

Classification ETIM 5: ETIM 5.0 Class-ID: EC001175

ETIM 5.0 Class-Description: Corrugated plastic hose

Classification ETIM 6: ETIM 6.0 Class-ID: EC001175

ETIM 6.0 Class-Description: Corrugated plastic hose

Colour delivered: Black (RAL 9005), UV-resistant

Material: PA 6

Halogen-free

Fire behaviour according to UL 94 V-2

Temperature range: -40°C to +120°C

#### Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products. Prices are net prices without VAT and surcharges. Sale to business customers only.

# SILVYN® TC

Article number	Nominal size	ID x OD mm	Metric size	PU ring (m)
64400823	7.5	6.6 x 10	10 x 1,5	50
64400824	8.5	9.8 x 12.8	12 x 1.5	50
64400825	12	12.3 x 15.7	16 x 1.5	50
61221035	17	16.6 x 21.2	20 x 1.5	50
64400650	22	23.1 x 28.4	25 x 1.5	50
64400651	26	28.9 x 34.5	32 x 1.5	50
64400826	37	34 x 42.2	40 x 1.5	50
64400827	50	45.6 x 52.8	50 x 1.5	50