

EPIC® H-B 6 TSH

Housing design H-B. The industry standard.


The robust metal housing with pivots for a single lever and a side cable entry is suitable for use in the plastics industry and investment construction.

Info

Non-slip ridges for comfortable disconnecting More interior space for wiring Protection rating UL50E tested













Supplementary automation components from Lapp



Mechanical and plant engineering



Mechanical resistance



Robust



Waterproof

The smallest housing out of the H-B series. For inserts with high electrical properties

Application range

Plant engineering Control engineering Plastics industry



EPIC® H-B 6 TSH

Product features

Hood, high version Bolts for single lever Side cable entry Versions with / without neck

Technical Data

Classification ETIM 5: ETIM 5.0 Class-ID: EC000437

ETIM 5.0 Class-Description: Housing for industrial connectors

Classification ETIM 6: ETIM 6.0 Class-ID: EC000437

ETIM 6.0 Class-Description: Housing for industrial connectors

Material: Housing: powder-coated aluminium alloy, grey

Bolts: steel, coated

Protection rating: IP 65 (latched)

NEMA 250, UL50E: 12, 4 (latched)

VDE-tested: Certified production control: VDE-REG. no.: B437

UL-tested:

UL File Number: E75770

Temperature range: -40°C to +100°C, short-term up to +125°C

Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products. Prices are net prices without VAT and surcharges. Sale to business customers only.



EPIC® H-B 6 TSH

Article number	Article description	M	PG	Neck	Pieces / PU
H-B housing: hood (side cable entry, bolts for single lever, high version)					
70022200	H-B 6 TSH 21	-	21	yes	10
70022400	H-B 6 TSH 29	-	29	yes	10
79022200	H-B 6 TSH M25	25	-	-	10
79022400	H-B 6 TSH M32	32	-	-	10