

CAT. N° 0 280 84



## AIR CIRCUIT BREAKER DMX<sup>3</sup> 1600 DRAW-OUT VERSION - BREAKING CAPACITY 50KA - 3P - 1250A

Pack (number of units)	O/R
Volume (dm <sup>3</sup> )	O/R
Weight (g)	O/R

### Product characteristics

#### Draw-out version

- Supplied with :
  - 4 auxiliary contacts: NO/NC
  - door sealing
- To be installed on a draw-out base Cat.No 0 281 53 or 0 281 54

#### Breaking capacity Icu 50 kA (415 V~)

- Frame 1600
- 3P
- In : 1250 A

### General characteristics

#### Air circuit breakers DMX<sup>3</sup> 1600 - from 630 to 1600 A

- Automatic air circuit breakers must be equipped with DMX<sup>3</sup> 1600 electronic protection units Cat.No 0 281 64/65/66, imperatively ordered together for factory assembly
- Please ask for DMX<sup>3</sup> order form
- Conform to IEC 60947-2

### Documentation

#### Catalogue pages & additional information

- [Description page \(p.156\)](#)

#### Installation & technical data

- [F02194EN\\_04\\_DMx3\\_1600v0](#)
- [LE10707AA](#)
- [EXB20072\\_logic\\_selectivity \(print\)](#)

#### Installation instructions & related documents

- [LE08437AC](#)