

CAT. N° 0 775 99



## FLUSH-MOUNTED WIRELESS CHARGER FOR PUBLIC AREA 1 A - 5 V/5 W - IK08 IP66

Pack (number of units)	1
Volume (dm <sup>3</sup> )	1,516
Weight (g)	330,00

### Product characteristics

#### Flush-mounted wireless chargers - for public area

- 1 A - 5 V/5 W wireless charger.
- Specially designed for public buildings, passageways or transit areas, swimming pools, etc.
- IK 08 - IP 66 - Class II SELV
- Comes with 2 induction antennae for fast smartphone charging.  
Recognition area: 50 x 80 mm
- Plate at an angle of 10° with non-slip coating to hold the terminal safely in place during charging
- Screws onto flush-mounting box with 60 mm fixing centres, min. depth 40 mm, French, German or British standard.
- Can also be fixed at 4 points
- Can be mounted on rectangular boxes and outdoors 110/230 VA Phase + Neutral power supply
- Mechanism supplied with cover plate, attached with 2 Torx screws at the side
- Aluminium colour
- Dimensions: 141 x 95 x 51 mm
- 2 x 2.5 mm<sup>2</sup> terminals

### General characteristics

#### Mosaic™ Programme mechanisms - wireless power chargers

- Wireless power chargers for fast charging a smartphone with a Qi receiver
- Power supply standby mode consumption less than 0.07%
- Conform to the Qi WPC standard (Wireless Power Consortium): certified for professional Qi 1.2.3 projects
- Conform to EN 62479 standard (EMF emissions)
- Conform to ICNIRP specifications (health protection)
- Do not interfere with other wireless signals (Zigbee, TNT, GSM, 4G, etc)

### Documentation

#### Catalogue pages & additional information

- [Description page \(p.461\)](#)
- [Description page \(p.886\)](#)

#### Installation & technical data

- F02378EN-01

#### Installation instructions & related documents

- [LE09643AE](#)

#### Agreements & certificates of conformity

- [OC / CB-SG ITS-17264](#)