

CAT. N° 4 092 29



## MCB - DX<sup>3</sup> 10000 - 16 KA - 2P - 230/400 V~ - 100 A - C CURVE

Pack (number of units)	1
Volume (dm <sup>3</sup> )	0,605
Weight (g)	471,00

### Product characteristics

#### 2-pole 230/400 V~

- C curve
- Nominal rating In : 100 A
- Number of modules : 3

### General characteristics

#### MCBs DX<sup>3</sup> 10000 - 16 kA - thermal magnetic circuit breakers from 1 A to 125 A - B and C curves

- Conform to IEC 60898-1
- Compatible with prong-type and fork type supply busbars (except 80 A, 100 A and 125 A MCBs)
- Breaking capacity
  - 10000 - IEC 60898-1 - 400 V~
  - 16 kA - IEC 60947-2 - 400 V~
- Can be equipped with DX<sup>3</sup> signalling and remote tripping auxiliaries, motorised controls and add-on modules

### Documentation



#### Catalogue pages & additional information

- [Description page \(p.066\)](#)
- [Dimensions of din-rail equipment](#)
- [Performance of MCBs and auxiliaries](#)



#### Installation & technical data

- [F01204EN-01](#)



#### Installation instructions & related documents

- [LE03603AG](#)



#### Environmental product profile

- [Environnemental product sheet n°8 E0084A-FR](#)
- [LGRP-00828-V01](#)