

Product designation				Rotary cam switches
Product type designation				GN20
General characteristics				
Switching diagram				14
Contact characteristics				
Rated insulation voltage U_i	IEC/EN	V	690	
	UL/CSA	V	600	
Rated impulse withstand voltage U_{imp}			kV	6
Conventional free air thermal current I_{th}	IEC/EN	A	20	
	UL/CSA	A	20	
Rated operational voltage			V	480
Maximum fuse size for short-circuit protection I_n (gG)	10kA	A	20	
	25kA	A	16	
Rated short time current I_{cw}			1s	A
				250
Operational current I_e IEC/EN	AC1/AC21A			A
	AC15			20
Rated operational power in AC	110V			A
	220/230V			10
	380/400V			A
	660/690V			8
				6
Three-phase AC-3	220/230V			kW
	380/440V			3
	500/690V			kW
Single-phase AC-3	110V			kW
	220/230V			0.8
	380/440V			kW
Three-phase AC23A	220/230V			kW
	380/440V			5
	500/690V			kW
Single-phase AC23A	110V			kW
	220/230V			0.8
	380/440V			kW
Rated operational current in DC	48V			A
	60V			20
	110V			A
	220V			4
	440V			A
DC21A				0.6
				0.25
DC23A (poles in series)	24V			A
				20 (1)

48V	A	20 (2)
60V	A	20 (3)
110V	A	10 (3)
220V	A	8 (4)

DC13

24V	A	20
48V	A	16
60V	A	12
110V	A	1
220V	A	0.4
440V	A	0.15

Mechanical features

Terminals screw M3

Tightening torque for terminals max Nm 0.5

Conductor size

AWG - Rigid cable

min	AWG	20
Max	AWG	12

AWG - Flexible cable

min	AWG	20
Max	AWG	14

Conductor size (IEC) - Flexible cable

min	mm ²	0.5
-----	-----------------	-----

Conductor size (IEC) - Rigid cable

Max	mm ²	2.5
-----	-----------------	-----

Mechanical life cycles 5x10⁶

UL technical data

Motor power for direct-on-line control

for three-phase motor

240V	HP	3
------	----	---

Ambient conditions

Temperature

Operating temperature

min	°C	-25
max	°C	+55

Storage temperature

min	°C	-40
max	°C	+70

Resistance & Protection

Frontal IP degree IP40

Terminals IP degree IP00

ETIM classification

ETIM 8.0

EC001029 -
Selector switch,
complete