

## MODLINK MSDD SINGLE COMBI INSERT USA NEMA 1-15

1xSUD-D25 female/male + 1xRJ45 female/female

USA (NEMA 5-15); SUB-D25; RJ45

1 × NEMA 1-15 (plug-solder connection)

1 × SUB-D25 (female/male)

1 × RJ45, 8-pole metal, CAT5e (female/female)

### [Link to Product](#)

#### Illustration



Product may differ from Image

#### Approvals



#### General data

Dimensions H × W × D 88×51×30 mm

#### SUB-D25

|                               |                        |
|-------------------------------|------------------------|
| Operating voltage             | 48 V AC/DC             |
| Operating voltage (UL Rating) | max. 30 V AC/42.4 V DC |
| Operating current             | 3 A                    |
| Operating current (UL Rating) | max. 175 mA            |
| No. of poles                  | 25-pole                |
| Connection front side         | SUB-D (female)         |
| Connection rear side          | SUB-D (male)           |

Locking of ports UNC 4...40 bolt

**RJ45**

Operating voltage (UL Rating) max. 30 V AC/42.4 V DC

Operating current (UL Rating) max. 175 mA

Connection front side RJ45

Connection rear side RJ45

Locking of ports Snap In

Specification CAT5e, Class D, 100 MHz, (EN 50173-1)

**USA**

Operating voltage 125 V AC

Operating current 15 A

No. of poles 2 + PE

Connection Plug-solder connection: 4.8 × 0.5 mm

**Commercial data**

country of origin DE

customs tariff number 85366990

EAN 4048879037242

eClass 27189217

Packaging unit 1