

stay connected

SUPPRESSOR FOR SIEMENS CONTACTOR S00 MOTOR

RC, star, 3x575 VAC, 7.5 kV


3× 575 V AC RC

Suppressors for other voltages, frequencies, and motor ratings available on request. Do not use RC motor suppressors with frequency inverters.

Link to Product

Illustration





RC

Product may differ from Image

Approvals



| T | е | С | h | ni | С | a | I | a | ta |
|---|---|---|---|----|---|---|---|---|----|
| | | | | | | | | | |

| Parities and a second | 2-component engry |
|-----------------------|---|
| Material | Flame retardant plastic acc. to (UL 94) |
| Frequency | 5060 Hz |

Potting compound 2-component epox

General data

The information in this brochure has been compiled with the utmost care.

Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 06/20



stay connected

| Connection wires | | | | |
|---|--|--|--|--|
| snap on Siemens Schütz Sirius 3 RT 201 with spring connention | | | | |
| -20+60 °C | | | | |
| 42×45×31 mm | | | | |
| | | | | |
| CZ | | | | |
| 85363010 | | | | |
| 4048879412742 | | | | |
| 27371013 | | | | |
| 1 | | | | |
| | | | | |