

MODLINK MSDD DATA INSERT

1×SUB-D9 fem./male + 1×RJ45 + 1×BNC female/female

BNC; RJ45; SUB-D9

1× BNC (female/female)

1× RJ45, 8-pole metal, CAT5e (female/female)

1× SUB-D9 (female/male)

[Link to Product](#)**Illustration**

Product may differ from Image

General data

Dimensions H×W×D 88×51×33 mm

RJ45

Operating voltage (UL Rating) max. 30 V AC/42.4 V DC

Operating current (UL Rating) max. 175 mA

Connection front side RJ45

Connection rear side RJ45

Locking of ports Snap In

Specification CAT5e, Class D, 100 MHz, (EN 50173-1)

BNC

Operating voltage (UL Rating) max. 30 V AC/42.4 V DC

Operating current (UL Rating) max. 175 mA

No. of poles 2 + PE

Connection front side BNC (female)

Connection rear side BNC (female)

Locking of ports Snap In

SUB-D9

Operating voltage 48 V AC/DC

Operating voltage (UL Rating) max. 30 V AC/42.4 V DC

Operating current 3 A

Operating current (UL Rating) max. 175 mA

No. of poles 9-pole

Connection front side SUB-D (female)

| | |
|----------------------|-----------------|
| Connection rear side | SUB-D (male) |
| Locking of ports | UNC 4...40 bolt |

Commercial data

| | |
|-----------------------|---------------|
| country of origin | DE |
| customs tariff number | 85366990 |
| EAN | 4048879037396 |
| eClass | 27189217 |
| Packaging unit | 1 |