

S-Switch 30 S 2NO 1x90LO M12(4)

Select switch 1x90° locked

S-Switch 30 S 2NO 1x90LO M12(4)

Select switch 1x90° locked

Connection M12 (4-pin)

Fronting stainless steel

Mounting hole 30,3 mm

[Link al prodotto](#)**Immagine**

Immagine rappresentativa

**Mechanical protection**

| | |
|---------------------------------------|---------|
| UL Enclosure Type Rating (Front side) | type 4X |
| Mechanical endurance | 200000 |
| Mechanical endurance B10 | 250000 |

Dati elettrici

| | |
|---|--------------------------------------|
| Corrente di cortocircuito | 1000 A |
| Kind of short circuit protective device | fuse 250 V / 0.1 A / 1.5 kA gG quick |
| Corrente di commutazione | 1...100 mA |
| Rated voltage UL 60947 | ≤ 30 V AC/DC |
| Tensione commutabile | 1...32 V |
| Commutazione (a seconda della tensione) | 0,25 W |
| Picco di tensione nominale | 2500 V |
| Tensione di isolamento nominale | 250 V |

caratteristiche ambientali

| | |
|----------------------------------|----------------|
| Salt-spray resistance | IEC 60068-2-11 |
| Altitudine di installazione max. | ≤ 2000 m |
| Umidità relativa | ≤ 93% @ 40 °C |
| temperatura di stoccaggio | -40...90 °C |
| temperatura di esercizio | -40...85 °C |

Mechanical data

| | |
|---|---------------------|
| Grid min. | 35 mm |
| Mounting hole | 30,3 mm |
| Mounting depth | 36,3 mm |
| Dimensioni HxLxP | 34,5 x 53,9 mm |
| Terminal | M12, 4 poli, A-code |
| Fixing | Threaded ring |
| Materiale contatto | Gold |
| Contact function | 2 S |
| Custodia | Plastica |
| Product article number of manufacturer | 69121 |
| Degree of protection (IP, EN 60529, front side) | IP65 |
| Degree of protection (IP, EN 60529, rear side) | IP65 |
| Alimentazione | |
| Rated operating current I _e | 0,1 A |
| Rated operating voltage (AC-15) | 35 V |
| Rated operating voltage (DC-13) | 35 V |
| Mechanical data | |
| Installation height | 17,6 mm |
| Mechanical data | |
| Can be illuminated | no |
| Collar shape | round |
| Color | nero |
| Bezel color | bianco |
| Collar color | nero |
| Color of front ring | nero |
| Actuating function | latching |