

PRODUCT-DETAILS

# 6131/40-24-500

## 6131/40-24-500 KNX Motion Detector Sky W



### Informazioni generali

Tipo	6131/40-24-500
ID prodotto	2CKA006132A0350
EAN	4011395185971
Descrizione catalogo	6131/40-24-500 KNX Motion Detector Sky W

Descrizione	<p>Detection range (for mounting height 6 m and 12 m): circular. Walking persons Ø: max. 18 m and 24 m. Visible height 23 mm. With 2 channels. Targeted for connection and disconnection of lights bands depending on the room brightness. Use of the device as a movement detector. Detectors application with 2 power off stages. Detectors application with integrated monitoring function. Constant light switch with up to two independent channels. Constant light switch with max. 2 outputs for brightness-dependent switching of two light bands in the area. With integrated KNX bus coupler.</p> <p>The programming button can be activated with the IR transmitter 6010-25 (-500). Suitable for false ceilings with a board thickness from 9 to 25 mm. Hole size: Ø 68 mm. Suitable for surface mounting installation. Cannot be installed in British Standard or VDE flushmounted box. Recommendation: Installation housing from Kaiser HaloX-O (Art.no. 1290-40) with corresponding cover plates (1290-47 or 1290-85 for fair faced concrete) or IBTronic H120-68 from Spelsberg.</p>
-------------	---

### Installation

Istruzioni e manuali	No document needed
----------------------	--------------------

## Circular Value

Circular Design Principles Lifetime	2CKA000073B5454
Group Waste to Landfill Target	No non-hazardous waste is sent to a landfill
Sustainable Material Content in Packaging	FSC Recycled Paperboard - 90 %
Improved Resource Efficiency for Customers	Digital Efficiency - Product is digitally-supported to optimize usage and eventually optimize customer asset
Offered with Extended Lifetime	Product Upgradability
Offered with Takeback Services	Take Back for Recycling

## Eco Transparency

Dichiarazione prodotto ambientale - EPD	9AKK108468A1033
---	-----------------

## Dati tecnici

Scheda tecnica	2CKA006132D0202
Intervallo di misura	24 m
Numero di canali	2
Sistemi bus compatibili	KNX (TP)
Gamma prodotto	KNX
Minimum Switching Time	Switch-On 10 secondo [unità di misura del tempo]
Tipo di montaggio	Surface Mounted Flush Mounted
Finitura superficie	Surface protection: Untreated Surface finishing: Matt
Materiale	Thermoplastic
Posizione di montaggio	Ceiling
Model Number	Movement sensor
RAL Number	RAL 9016 - Bianco traffico
Colore	studio white matt
Number of Batteries	0
Application Function	Electrical Load and Light Control

## Dati ambientali

Temperatura ambiente	In funzione -5 ... +45 °C
Grado di protezione	IP20
Dichiarazione RoHS	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Informazioni RoHS	2CKA200000E4528
REACH Declaration	2CKA309999E9999
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

## Dimensioni

Larghezza prodotto	91 mm
--------------------	-------

Altezza prodotto	91 mm
Profondità prodotto	45 mm
Peso netto prodotto	110.5 g
Profondità integrata (t <sub>2</sub> )	22 mm

## Ordinazione

ID prodotto sostituito (VECCHIO)	6132-0-0350
----------------------------------	-------------

## Certificati e dichiarazioni (numero del documento)

Dichiarazione di conformità - CE	2CKA100000E1061
----------------------------------	-----------------

## Classificazioni

ETIM 8	EC001582 - Movement sensor for bus system
ETIM 9	EC001582 - Movement sensor for bus system
Categoria RAEE	5. Piccole apparecchiature (nessuna dimensione esterna superiore a 50 cm)
CN8	Business To Consumer
Tipo di oggetto design	8536 50 80
eClass	V11.0 : 27143144

## Accessories

Identifier	Description	Type	Quantity	Unit Of Measure
2CKA006132A0403	6131/38-24-500 Intermediate ring fm box W	6131/38-24-500	1	pezzo (i)
2CKA006899A2304	Protection Cover	6898	1	pezzo (i)

## Categorie

Prodotti di bassa tensione → Automazione case ed edifici → KNX → Presence Detection → Presence Detectors

