

PRODUCT-DETAILS

6817/33-24-500

Presence Detector 12 m 200 W



Informazioni generali

Tipo	6817/33-24-500
ID prodotto	2CKA006800A2743
EAN	4011395217658
Descrizione catalogo	Presence Detector 12 m 200 W

Descrizione

Master presence detector with mixed light measurement. For switching lighting systems that depend on brightness and movement. With Bluetooth interface for parameterization and operation. Adjustment of all setting options via smartphone or tablet. Light control via smartphone or tablet app. With electronic switch contact for LED operation. With selectable soft ON/OFF function. Detection range (for installation height of 3 m): circular Seated persons: up to Ø 10 m, walking persons: up to Ø 12 m. Extension of the detection range by means of master/slave combination. Visible height 23 mm. For semi-automatic, comfort and fully automatic operation. Additional activation/deactivation possibility through pushbutton input. With continuous light/continuous off function (8 hours), activation via intelligent extension unit input possible. With selectable presence simulation in case of non-presence. With integrated storage of ON period (energy monitor). With brightness-independent test mode for evaluating the detection zone. With detection display in test mode. Ceiling installation using integrated spring bracket. Twist protection via additional quick tensioning. Adjustment elements accessible on the front side. Surveillance density: 72 sectors with 640 switching segments. Individual deactivation and adjustment of sensitivity of individual sensors possible. Switch-off delay: approx. 1 min. - 30 min. or short-time pulse adjustable. With selectable dynamic switch-off delay.

Installation

Dati tecnici

Scheda tecnica	2CKA001673B9577
Funzione	Setting Options by Bluetooth
Tensione nominale (U _r)	230 V AC
Tensione ausiliaria AC/DC	110 V AC/DC 230 V AC/DC
Tipo di tensione d'ingresso	AC
Range di corrente	Maximum 350 A
Frequenza (f)	50...60 Hz
Frequenza nominale (f)	50 / 60 Hz
Potenza massima di commutazione	200 W
Perdita di potenza	0.3 W
Intervallo di misura	12 m
Numero di uscite	1
Number of Switching Zones	640
Tempo di ritardo (T)	Off 0 secondo [unità di misura del tempo] On 0 secondo [unità di misura del tempo]
Minimum Switching Time	Switch-On 60 secondo [unità di misura del tempo]
Tipo di connessione	Plug Clamp
Tipo di carico	230 V incandescent lamps
Tipo di montaggio	Built-in
Tipo sensore	Passive infrared
Finitura superficie	Surface protection: Untreated Surface finishing: Matt
Materiale	Plastic Thermoplastic
Posizione di montaggio	Ceiling
Illuminamento	5 ... 2000 lx
Model Number	Presence detector
RAL Number	RAL 9016 - Bianco traffico
Colore	studio white matt
Application Function	Electrical Load and Light Control

Dati ambientali

Temperatura ambiente	In funzione -5 ... +45 °C
Grado di protezione	IP40
Dichiarazione RoHS	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Informazioni RoHS	2CKA200000E6490
REACH Declaration	2CKA309999E9999
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Dimensioni

Larghezza prodotto	94 mm
--------------------	-------

Altezza prodotto	94 mm
Profondità prodotto	59 mm
Peso netto prodotto	143.2 g
Profondità integrata (t ₂)	36 mm

Certificati e dichiarazioni (numero del documento)

Dichiarazione di conformità - CE	2CKA200000E6490
----------------------------------	-----------------

Classificazioni

ETIM 8	EC000133 - Movement sensor complete
ETIM 9	EC000133 - Movement sensor/presence detector complete
Categoria RAEE	5. Piccole apparecchiature (nessuna dimensione esterna superiore a 50 cm)
CN8	Business To Consumer
Tipo di oggetto design	8536 50 80
eClass	V11.0 : 27144007

Accessories

Identifier	Description	Type	Quantity	Unit Of Measure
2CKA006800A2765	Presence Detector	6889/30-24-500	1	pezzo (i)
2CKA006499A0002	Extension Module	6494-500	1	pezzo (i)
2CKA006899A2304	Protection Cover	6898	1	pezzo (i)

Categorie

Prodotti di bassa tensione → Wiring Accessories - StandAlone Electronics → Presence Detector → Professional Series

